

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sales No. : Stemone - GIVAUDAN

Substance name : 5-METHYL-3-HEPTANONE OXIME
Identifier

CAS-No. : 22457-23-4
EC-No. : 245-010-8
Formula : C8-H17-N-O
REACH Registration Number : 01-2120747610-59

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended Use Fragrances : Perfumery ingredient

1.3 Details of the supplier of the safety data sheet

Company :
Givaudan Suisse SA
Chemin de la Parfumerie 5
CH-1214 VERNIER

Telephone : +41227809111
Telefax : +41227809150
E-mail address : global.sds_info@givaudan.com
Responsible/issuing person

1.4 Emergency Call

Givaudan 24/7 call : +33172110003

Please refer to section 16 for a full list of emergency phone numbers, from Givaudan's 24/7 provider.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements	: H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	: Prevention: P273 Disposal: P501	Avoid release to the environment. Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

Hazards not Otherwise Classified : None

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

3.1 Substances

Chemical name	CAS-No. EC-No. REACH Registration Number	Concentration [Percent by weight]	M-Factor, SCL, ATE
5-methyl-3-heptanone oxime	22457-23-4 245-010-8 01-2120747610-59	>= 90 - <= 100	Acute toxicity estimate Acute oral toxicity:3 800,00 mg/kg

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

SECTION 4. First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
If on skin, rinse well with water.
- In case of eye contact : Remove contact lenses.
Immediately flush eyes for at least 15 minutes. Get medical attention.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : no data available
Risks : no data available

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : no data available

SECTION 5. Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry chemical
Alcohol-resistant foam
Carbon dioxide (CO₂)
Water spray
- Unsuitable extinguishing media : no data available

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : no data available

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

Not applicable

SECTION 7. Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Temperature class : no data available
- Fire-fighting class : no data available
- Dust explosion class : no data available

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Further information on storage conditions : Store Ambient 10-30°C (50-85°F)
Dry, well ventilated, preferably full, hermetically sealed
Advice on common storage : Protect against light.
Storage class (TRGS 510) : 10 Combustible liquids
Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Please refer to attached exposure scenarios.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

DNEL : End Use: Consumer use
Exposure routes: Dermal
Potential health effects: Acute local effects
Value: 25,0 mg/cm²

DNEL : End Use: Consumer use
Exposure routes: Dermal
Potential health effects: Acute systemic effects
Value: 10,0 mg/kg bw/day

DNEL : End Use: Consumer use
Exposure routes: Dermal
Potential health effects: Long-term local effects
Value: 25,0 mg/cm²

DNEL : End Use: Consumer use
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 10,0 mg/kg bw/day

DNEL : End Use: Consumer use
Exposure routes: Inhalation
Potential health effects: Acute local effects
Value: 43,48 mg/m³

DNEL : End Use: Consumer use
Exposure routes: Inhalation
Potential health effects: Acute systemic effects
Value: 17,39 mg/m³

DNEL : End Use: Consumer use

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Givaudan

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

		Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 43,48 mg/m ³
DNEL	:	End Use: Consumer use Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 17,39 mg/m ³
DNEL	:	End Use: Consumer use Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 10,0 mg/kg bw/day
DNEL	:	End Use: Workers Exposure routes: Dermal Potential health effects: Acute local effects Value: 50,0 mg/cm ²
DNEL	:	End Use: Workers Exposure routes: Dermal Potential health effects: Acute systemic effects Value: 20,0 mg/kg bw/day
DNEL	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 50,0 mg/cm ²
DNEL	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20,0 mg/kg bw/day
DNEL	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 176,32 mg/m ³
DNEL	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 70,53 mg/m ³
DNEL	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 176,32 mg/m ³

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

DNEL	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 70,53 mg/m3
PNEC	:	Fresh water Value: 0,044 mg/l
PNEC	:	Marine water Value: 0,0044 mg/l
PNEC	:	Fresh water sediment Value: 0,88 mg/kg dry weight (d.w.)
PNEC	:	Marine sediment Value: 0,088 mg/kg dry weight (d.w.)
PNEC	:	Soil Value: 0,15 mg/kg dry weight (d.w.)
PNEC	:	Sewage treatment plant Value: 10,0 mg/l

8.2 Exposure controls

Exposure assessment: Exposures are dependent on the product being handled, the potential for chemical release, and any resulting airborne concentrations or dermal contact. Since product handling and release scenarios vary, and no two workplaces are exactly alike, it is recommended that the potential for exposure be assessed prior to the product's use or introduction. Exposure assessments should be performed by an occupational hygienist, industrial hygienist, or other qualified occupational or environmental health professional. An exposure assessment should be conducted to determine the efficacy of any ventilation and the need for additional PPE. The PPE indicated below are recommendations for worst-case scenario exposures. An exposure assessment will identify more applicable measures to be implemented. EN and ANSI standards are mentioned in the following recommendations, consult equivalent local standards when required.

PPE is always the last resort to avoid exposure. In any case technical and organisational measures have to be explored and used prior to the selection of PPE. The PPE selection is for operators trained to work with chemicals according to good industrial hygiene and safety practice. Operators have to be trained on the use of PPE.

8.2.1 Engineering measures

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Use engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use the product only with adequate ventilation.

8.2.2 Personal protective equipment

- Eye/face protection : Use safety glasses tested according to EN 166/ANSI Z87.1 or equivalent local standard.
- Hand protection : Use gloves when handling substance in open systems. Inspect gloves prior to use. Train operators for proper use. If only incidental exposure is expected: (work without direct contact to substance) use gloves tested according EN 16523-1/ASTM F739 or equivalent local standard breakthrough times at least 10 minutes, tested for chemicals indicated in chapter 3 of this SDS. Change gloves frequently. If direct skin contact is expected: use gloves tested according to EN 16523-1/ASTM F739 or equivalent local standard, tested for chemicals indicated in chapter 3 of this SDS. Permeation time must exceed contact time.
- Other skin protection : Wear working clothes covering arms and legs.
- Respiratory protection : Under normal use conditions, no respiratory protection should be needed. However, if discomfort is experienced, use an approved air-purifying respirator.
- Thermal hazards : Wear appropriate thermal protective clothing, when necessary.
- Hygiene measures : Remove contaminated clothing and protective equipment before entering eating areas.
Do not eat, drink or smoke during work.
Wash hands any time after handling the product.

8.2.3 Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Form : liquid
Colour : colorless to Pale yellow

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Taste	: not determined
Odour	: Green, Powerful, Dry, fruity
Odour Threshold	: 14 ng/l
Flash point	: 97 °C Method: closed cup
Lower explosion limit	: not determined
Upper explosion limit	: not determined
Flammability	: no data available
Particle size	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing. Information taken from reference works and the literature.
Auto-ignition temperature	: 288 °C Auto-ignition temperature Method: A15
Decomposition temperature	: no data available
Molecular weight	: 143,20 g/mol
pH	: no data available
Melting point	: < -20 °C
Boiling point	: 211 °C at 1 013 hPa
Vapour pressure	: 0,096 hPa at 25 °C Method: OECD Test Guideline 104
Density	: 889,39 kg/m ³ at 20 °C
Bulk density	: Not applicable
Water solubility	: 1 060 mg/l at 20 °C
Solubility/qualitative	: Very slightly soluble
Partition coefficient: n-octanol/water	: log Pow: 2,3 Method: OECD Test Guideline 117
Viscosity, kinematic	: no data available
Relative vapour density	: no data available
Surface tension	: 45,3 mN/m at 20 °C Method: OECD Test Guideline 115
Evaporation rate	: no data available
Explosive properties	: Not explosive

9.2 Other information

Not applicable

SECTION 10. Stability and reactivity

10.1 Reactivity

none

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No hazards

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : no data available

10.5 Incompatible materials

Materials to avoid : no data available

10.6 Hazardous decomposition products

Hazardous decomposition products : no data available

Thermal decomposition : no data available

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity : LD50 Rat
Dose: 3 500 mg/kg

Acute inhalation toxicity : This information is not available.

Acute dermal toxicity : LD50 Rabbit
Dose: > 5 000 mg/kg

Acute toxicity (other routes of administration) : No data is available on the product itself.

Skin corrosion/irritation

Skin irritation : Species: Guinea pig
Mild skin irritation
Method: OECD Test Guideline 404

Serious eye damage/eye irritation

Eye irritation : No data is available on the product itself.

Respiratory or skin sensitisation

Sensitisation : Skin sensitization Guinea pig
Result: Not sensitizing

HRIPT Human
Result: Not sensitizing

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

at 2 % in Dimethyl phthalate

Germ cell mutagenicity

Genotoxicity in vitro : In vitro mammalian cell gene mutation test
negative
Method: OECD Test Guideline 476

Ames test
negative
Method: Mutagenicity (Salmonella typhimurium - reverse
mutation assay)

Carcinogenicity

Carcinogenicity : No data is available on the product itself.

Reproductive toxicity

Not classified based on available information.

Target Organ Systemic Toxicant - Single exposure

Target Organ Systemic Toxicant - Single exposure : No data is available on the product itself.

Target Organ Systemic Toxicant - Repeated exposure

Target Organ Systemic Toxicant - Repeated exposure : Species: Rat, male and female
Application Route: Dermal
NOAEL: 1 000 mg/kg
Method: OECD Test Guideline 422

Aspiration hazard

Aspiration toxicity : No data is available on the product itself.

Phototoxicity

Phototoxicity : Phototoxicity Guinea pig
Result:negative

Further information

: no data available

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : no data available

SECTION 12. Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 (Fish): 51,5 mg/l
Exposure time: 96 h
GLP: no
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 62 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 10 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

12.2 Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301 F
GLP: yes

Result: Not inherently biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302 C
GLP: yes

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

SECTION 13. Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.

Dispose of in accordance with local regulations.

SECTION 14. Transport information

14.1 UN number

N/A

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

N/A

14.4 Packing group

N/A

14.5 Environmental hazards

N/A

14.6 Special precautions for user

IMDG

IMDG Code Segregation : None
Group

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Neither banned nor restricted

Major Accident Hazard Legislation : Not applicable

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Water hazard class : WGK 2 obviously hazardous to water
(Germany) Code Number: 6 212
Classification according to AwSV, Annex 1 (4)

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16. Other information

Full list of Emergency response numbers worldwide.

	Country	Phone nr		Country	Phone nr
Europe	All Europe	+44 1235 239670	APAC	All East/South East Asia	+65 3158 1074
	France	+33 1 72 11 00 03		Sri Lanka	+65 3158 1195
	Germany	+49 89 220 61012		Taiwan	+886 2 8793 3212
	Spain	+34 91 114 2520		Japan	0120 015 230
	Italy	800 699 792		Indonesia	007 803 011 0293
	Netherlands	+31 10 713 8195		Malaysia	+60 3 6207 4347
	Turkey	0800 621 2139 +44 1235 239670		Thailand	001 800 120 666 751
	Norway	+47 2103 4452		India	+65 3158 1198 000 800 100 7479
	Greece	+30 21 1198 3182		Pakistan	+65 3158 1329
	Portugal	+351 30880 4750		Bangladesh	+65 3158 1200
	Denmark	+45 8988 2286		Philippines	+63 2 8231 2149
	Sweden	+46 8 566 42573		Vietnam	+84 28 4458 2388
	Poland	+48 22 307 3690		Korea	+65 3158 1285
	Czech republic	+420 228 882 830		South Korea	+82 2 3479 8401
Finland	+358 9 7479 0199	Australia	+61 2 8014 4558		
Middle East/Africa	All Middle East/Africa	+44 1235 239671	LATAM	New Zealand	+64 9 929 1483
	Bahrain and Middle East	+44 1235 239671		China	+86 532 8388 9090
	Africa/South Africa	+27 21 300 2732		Mexico	+52 55 5004 8763
NOAM	USA and Canada	+1 866 928 0789		Brazil	+55 11 3197 5891

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

	USA and Canada	+1 215 207 0061		Chile	+56 2 2582 9336
	USA and Canada	+1 202 464 2554		Colombia	+57 1 508 7337
Global	Global	+44 1865 407333		Argentina	+54 11 5984 3690

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Givaudan

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Key or legend to abbreviations and acronyms used in the safety data sheet

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Information displayed in section 3 (Composition/information on ingredients) is additional information to understand the hazards of the product and ensure safe handling, storage and transportation. This information, including CAS numbers, is not meant to be used for registration, notification or any other purposes. Any additional information and documentation needed may be provided by Givaudan.

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Annex

Exposure Scenario

Number	Title
ES1	Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds)
ES2	Formulation of fragranced end-products (mixing of fragrance compounds into fragranced end-products)
ES3	Industrial end-use of washing and cleaning products
ES4	Professional end-use of washing and cleaning products
ES5	Professional end-use of polishes and wax blends
ES6	Consumer end-use of washing and cleaning products
ES7	Consumer end-use of air care products
ES8	Consumer end-use of biocides
ES9	Consumer end-use of polishes and wax blends
ES10	Consumer (and Professional) end-use of cosmetics

1. ES 1: Formulation or re-packing; Other; Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds)

1.1. Title section

ES name: GES 1; Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds)
Product category: Other (PC 0)

Environment

1: GES 1; Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds); AISE ERC 2
SPERC 2.1.a.v1

Worker

2: CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; IFRA F-1	PROC 8b
3: CS2; Storage; IFRA F-2	PROC 1
4: CS3; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; IFRA F-3	PROC 3
5: CS4; Mixing operations; Open systems; Filling of articles/equipment; With sample collection; IFRA F-4	PROC 5
6: CS5; Laboratory activities; Use as laboratory reagent; IFRA F-5	PROC 15
7: CS6; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); IFRA F-6	PROC 9
8: CS7; Equipment cleaning and maintenance; IFRA F-7	PROC 8a

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: GES 1; Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds); AISE SPERC 2.1.a.v1 (ERC 2)

Amount used, frequency and duration of use (or from service life)

Annual amount per site <= 25 tonnes/year

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Daily amount per site <= 0.1 tonnes/day
Conditions and measures related to biological sewage treatment plant
Municipal sewage treatment plant is assumed.
application of the STP sludge on agricultural soil; Yes
Assumed domestic sewage treatment plant flow; >=; 2E3; m3/day
Other conditions affecting environmental exposure
Receiving surface water flow >= 1.8E4 m3/day

1.2.2. Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product (article) characteristics
Liquid
Technical and organisational conditions and measures
Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.; Ensure regular inspection, cleaning and maintenance of equipment and machines.; Clear spills immediately.; Ensure daily cleaning of the equipment.
Conditions and measures related to personal protection, hygiene and health evaluation
Respiratory protection; No.
Use suitable eye protection.
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.
Other conditions affecting workers exposure
Covers skin contact area up to ; One hand face only (240 cm2)
Indoor use
Assumes process temperature up to 40 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; IFRA F-1 (PROC 8b)	Covers concentrations up to 25 % Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Provide enclosing hood with very high effectiveness (such as fume cupboard) or effective ventilation by spray booth according to EN 16985. Ensure effectiveness is at least 95%.
CS2; Storage; IFRA F-2 (PROC 1)	Covers concentrations up to 0 % Covers use up to 1 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation; No.
CS3; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; IFRA F-3 (PROC 3)	Covers concentrations up to 100 % Covers use up to 4 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%
CS4; Mixing operations; Open systems; Filling of articles/equipment; With sample collection; IFRA F-4 (PROC 5)	Covers concentrations up to 100 % Covers use up to 4 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%
CS5; Laboratory activities; Use as laboratory reagent; IFRA F-5 (PROC 15)	Covers concentrations up to 100 % Covers use up to 0.25 h/day Room ventilation; Basic; Up to 3 air change per hour

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

	Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%
CS6; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); IFRA F-6 (PROC 9)	Covers concentrations up to 25 % Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%
CS7; Equipment cleaning and maintenance; IFRA F-7 (PROC 8a)	Covers concentrations up to 25 % Covers use up to 4 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: GES 1; Formulation of fragrance compounds (mixing of fragrance substances into fragrance compounds); AISE SPERC 2.1.a.v1 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.5 kg/day	Estimated release factor
Air	2.5 kg/day	ERC
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	0.025 mg/L (EUSES 2.1.2)	0.557
Sediment (freshwater)	0.49 mg/kg dw (EUSES 2.1.2)	0.557
Marine water	2.45E-3 mg/L (EUSES 2.1.2)	0.557
Sediment (marine water)	0.049 mg/kg dw (EUSES 2.1.2)	0.557
Sewage Treatment Plant	0.243 mg/L (EUSES 2.1.2)	0.024
Agricultural soil	0.073 mg/kg dw (EUSES 2.1.2)	0.483

1.3.2. Worker exposure: CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; IFRA F-1 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.179 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	3.581 mg/m ³ (TRA Workers 3.0)	0.051
Inhalation, local, long term	0.179 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	3.581 mg/m ³ (TRA Workers 3.0)	0.02
Dermal, systemic, long term	0.823 mg/kg bw/day (TRA Workers 3.0)	0.041
Dermal, local, long term	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.044

1.3.3. Worker exposure: CS2; Storage; IFRA F-2 (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	8.35E-4 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, long term	8.35E-4 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Dermal, systemic, long term	3.4E-4 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	9.92E-5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	9.92E-5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

1.3.4. Worker exposure: CS3; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; IFRA F-3 (PROC 3)

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.074 mg/m ³ (TRA Workers 3.0)	0.015
Inhalation, systemic, acute	7.161 mg/m ³ (TRA Workers 3.0)	0.102
Inhalation, local, long term	1.074 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	7.161 mg/m ³ (TRA Workers 3.0)	0.041
Dermal, systemic, long term	0.069 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.019

1.3.5. Worker exposure: CS4; Mixing operations; Open systems; Filling of articles/equipment; With sample collection; IFRA F-4 (PROC 5)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.79 mg/m ³ (TRA Workers 3.0)	0.025
Inhalation, systemic, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.169
Inhalation, local, long term	1.79 mg/m ³ (TRA Workers 3.0)	0.01
Inhalation, local, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.068
Dermal, systemic, long term	1.371 mg/kg bw/day (TRA Workers 3.0)	0.069
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.094

1.3.6. Worker exposure: CS5; Laboratory activities; Use as laboratory reagent; IFRA F-5 (PROC 15)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.298 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.169
Inhalation, local, long term	0.298 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.068
Dermal, systemic, long term	0.034 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	9.92E-3 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	9.92E-3 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

1.3.7. Worker exposure: CS6; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); IFRA F-6 (PROC 9)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.358 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	7.161 mg/m ³ (TRA Workers 3.0)	0.102
Inhalation, local, long term	0.358 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	7.161 mg/m ³ (TRA Workers 3.0)	0.041
Dermal, systemic, long term	0.412 mg/kg bw/day (TRA Workers 3.0)	0.021
Dermal, local, long term	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.026

1.3.8. Worker exposure: CS7; Equipment cleaning and maintenance; IFRA F-7 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.148 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	14.32 mg/m ³ (TRA Workers 3.0)	0.203
Inhalation, local, long term	2.148 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	14.32 mg/m ³ (TRA Workers 3.0)	0.081
Dermal, systemic, long term	0.823 mg/kg bw/day (TRA Workers 3.0)	0.041
Dermal, local, long term	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.06 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.072

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

2. ES 2: Formulation or re-packing; Other; Formulation of fragranced end-products (mixing of fragrance compounds into fragranced end-products)

2.1. Title section

ES name: GES 2; Formulation of fragranced end-products (mixing of fragrance compounds into fragranced end-products)

Product category: Other (PC 0)

Environment

1: IFRA SG-1; AISE SPERC 2.1.a.v2; AISE SPERC 2.1.g.v2	ERC 2
2: IFRA SG-2; AISE SPERC 2.1.b.v2; AISE SPERC 2.1.h.v2	ERC 2
3: IFRA SG-3; AISE SPERC 2.1.c.v2; AISE SPERC 2.1.i.v2	ERC 2
4: IFRA SG-4; AISE SPERC 2.1.j.v2; Cosmetics Europe / AISE SPERC 2.3.a.v2; Cosmetics Europe SPERC 2.1.a.v2	ERC 2
5: IFRA SG-5; AISE SPERC 2.1.k.v2; Cosmetics Europe / AISE SPERC 2.3.b.v2; Cosmetics Europe SPERC 2.1.b.v2	ERC 2
6: IFRA SG-6; AISE SPERC 2.1.l.v2; Cosmetics Europe / AISE SPERC 2.3.c.v2; Cosmetics Europe SPERC 2.1.c.v2	ERC 2
7: IFRA SG-7; Cosmetics Europe SPERC 2.2.a.v2; Cosmetics Europe SPERC 2.2.c.v2	ERC 2
8: IFRA SG-8; Cosmetics Europe SPERC 2.1.d.v2; Cosmetics Europe SPERC 2.1.j.v2	ERC 2

Worker

9: CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; AISE M-6	PROC 8b
10: CS2; Laboratory activities; Use as laboratory reagent; AISE M-9	PROC 15
11: CS3; Storage; AISE M-1	PROC 1
12: CS4; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; AISE M-3	PROC 3
13: CS5; Mixing or blending in batch processes; Open systems; With sample collection; AISE M-5	PROC 5
14: CS6; Equipment cleaning and maintenance	PROC 8a
15: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC 2
16: CS7; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); AISE M-7	PROC 9
17: CS8; Tableting, compression, extrusion or pelletisation; AISE M-8	PROC 14

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: IFRA SG-1; AISE SPERC 2.1.a.v2; AISE SPERC 2.1.g.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)
Daily amount per site <= 0.15 tonnes/day
Annual amount per site <= 37.5 tonnes/year
Conditions and measures related to biological sewage treatment plant
Assumed domestic sewage treatment plant flow, >=: 2E3; m3/day
application of the STP sludge on agricultural soil; Yes
Municipal sewage treatment plant is assumed.
Other conditions affecting environmental exposure
Receiving surface water flow >= 1.8E4 m3/day

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

2.2.2. Control of environmental exposure: IFRA SG-2; AISE SPERC 2.1.b.v2; AISE SPERC 2.1.h.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)
Daily amount per site <= 0.056 tonnes/day
Annual amount per site <= 14 tonnes/year
Conditions and measures related to biological sewage treatment plant
Assumed domestic sewage treatment plant flow; >=; 2E3; m3/day
application of the STP sludge on agricultural soil; Yes
Municipal sewage treatment plant is assumed.
Other conditions affecting environmental exposure
Receiving surface water flow >= 1.8E4 m3/day

2.2.3. Control of environmental exposure: IFRA SG-3; AISE SPERC 2.1.c.v2; AISE SPERC 2.1.i.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)
Daily amount per site <= 0.046 tonnes/day
Annual amount per site <= 11.5 tonnes/year
Conditions and measures related to biological sewage treatment plant
Assumed domestic sewage treatment plant flow; >=; 2E3; m3/day
application of the STP sludge on agricultural soil; Yes
Municipal sewage treatment plant is assumed.
Other conditions affecting environmental exposure
Receiving surface water flow >= 1.8E4 m3/day

2.2.4. Control of environmental exposure: IFRA SG-4; AISE SPERC 2.1.j.v2; Cosmetics Europe / AISE SPERC 2.3.a.v2; Cosmetics Europe SPERC 2.1.a.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)
Daily amount per site <= 0.042 tonnes/day
Annual amount per site <= 10.5 tonnes/year
Conditions and measures related to biological sewage treatment plant
Assumed domestic sewage treatment plant flow; >=; 2E3; m3/day
application of the STP sludge on agricultural soil; Yes
Municipal sewage treatment plant is assumed.
Other conditions affecting environmental exposure
Receiving surface water flow >= 1.8E4 m3/day

2.2.5. Control of environmental exposure: IFRA SG-5; AISE SPERC 2.1.k.v2; Cosmetics Europe / AISE SPERC 2.3.b.v2; Cosmetics Europe SPERC 2.1.b.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)
Daily amount per site <= 0.018 tonnes/day
Annual amount per site <= 4.5 tonnes/year
Conditions and measures related to biological sewage treatment plant
Assumed domestic sewage treatment plant flow; >=; 2E3; m3/day
application of the STP sludge on agricultural soil; Yes
Municipal sewage treatment plant is assumed.

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Other conditions affecting environmental exposure

Receiving surface water flow $\geq 1.8E4$ m³/day

2.2.6. Control of environmental exposure: IFRA SG-6; AISE SPERC 2.1.i.v2; Cosmetics Europe / AISE SPERC 2.3.c.v2; Cosmetics Europe SPERC 2.1.c.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)

Daily amount per site ≤ 0.018 tonnes/day

Annual amount per site ≤ 4.5 tonnes/year

Conditions and measures related to biological sewage treatment plant

Assumed domestic sewage treatment plant flow; $\geq 2E3$; m³/day

application of the STP sludge on agricultural soil; Yes

Municipal sewage treatment plant is assumed.

Other conditions affecting environmental exposure

Receiving surface water flow $\geq 1.8E4$ m³/day

2.2.7. Control of environmental exposure: IFRA SG-7; Cosmetics Europe SPERC 2.2.a.v2; Cosmetics Europe SPERC 2.2.c.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)

Daily amount per site ≤ 0.064 tonnes/day

Annual amount per site ≤ 16 tonnes/year

Conditions and measures related to biological sewage treatment plant

Assumed domestic sewage treatment plant flow; $\geq 2E3$; m³/day

application of the STP sludge on agricultural soil; Yes

Municipal sewage treatment plant is assumed.

Other conditions affecting environmental exposure

Receiving surface water flow $\geq 1.8E4$ m³/day

2.2.8. Control of environmental exposure: IFRA SG-8; Cosmetics Europe SPERC 2.1.d.v2; Cosmetics Europe SPERC 2.1.j.v2 (ERC 2)

Amount used, frequency and duration of use (or from service life)

Daily amount per site $\leq 6E-3$ tonnes/day

Annual amount per site ≤ 1.5 tonnes/year

Conditions and measures related to biological sewage treatment plant

Assumed domestic sewage treatment plant flow; $\geq 2E3$; m³/day

application of the STP sludge on agricultural soil; Yes

Municipal sewage treatment plant is assumed.

Other conditions affecting environmental exposure

Receiving surface water flow $\geq 1.8E4$ m³/day

2.2.9. Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product (article) characteristics

Liquid

Technical and organisational conditions and measures

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Room ventilation; Basic; Up to 3 air change per hour
Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.; Ensure regular inspection, cleaning and maintenance of equipment and machines.; Clear spills immediately.; Ensure daily cleaning of the equipment.

Local exhaust ventilation; No.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS.

Respiratory protection; No.

Use suitable eye protection.

Other conditions affecting workers exposure

Indoor use

Assumes process temperature up to 40 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; AISE M-6 (PROC 8b)	Covers concentrations up to 25 % Covers use up to 1 h/day
CS2; Laboratory activities; Use as laboratory reagent; AISE M-9 (PROC 15)	Covers concentrations up to 25 % Covers use up to 0.25 h/day
CS3; Storage; AISE M-1 (PROC 1)	Covers concentrations up to 25 % Covers use up to 1 h/day
CS4; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; AISE M-3 (PROC 3)	Covers concentrations up to 25 % Covers use up to 4 h/day
CS5; Mixing or blending in batch processes; Open systems; With sample collection; AISE M-5 (PROC 5)	Covers concentrations up to 25 % Covers use up to 4 h/day
CS6; Equipment cleaning and maintenance (PROC 8a)	Covers concentrations up to 1 % Covers use up to 4 h/day
Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)	Covers concentrations up to 25 % Covers use up to 1 h/day
CS7; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); AISE M-7 (PROC 9)	Covers concentrations up to 1 % Covers use up to 1 h/day
CS8; Tableting, compression, extrusion or pelletisation; AISE M-8 (PROC 14)	Covers concentrations up to 1 % Covers use up to 8 h/day

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: IFRA SG-1; AISE SPERC 2.1.a.v2; AISE SPERC

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

2.1.g.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.015 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	9.63E-4 mg/L (EUSES 2.1.2)	0.022
Sediment (freshwater)	0.019 mg/kg dw (EUSES 2.1.2)	0.022
Marine water	9.52E-5 mg/L (EUSES 2.1.2)	0.022
Sediment (marine water)	1.9E-3 mg/kg dw (EUSES 2.1.2)	0.022
Sewage Treatment Plant	7.29E-3 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	2.14E-3 mg/kg dw (EUSES 2.1.2)	0.014

2.3.2. Environmental release and exposure: IFRA SG-2; AISE SPERC 2.1.b.v2; AISE SPERC 2.1.h.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.056 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	2.95E-3 mg/L (EUSES 2.1.2)	0.067
Sediment (freshwater)	0.059 mg/kg dw (EUSES 2.1.2)	0.067
Marine water	2.94E-4 mg/L (EUSES 2.1.2)	0.067
Sediment (marine water)	5.89E-3 mg/kg dw (EUSES 2.1.2)	0.067
Sewage Treatment Plant	0.027 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	7.89E-3 mg/kg dw (EUSES 2.1.2)	0.053

2.3.3. Environmental release and exposure: IFRA SG-3; AISE SPERC 2.1.c.v2; AISE SPERC 2.1.i.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.092 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	4.7E-3 mg/L (EUSES 2.1.2)	0.107
Sediment (freshwater)	0.094 mg/kg dw (EUSES 2.1.2)	0.107
Marine water	4.69E-4 mg/L (EUSES 2.1.2)	0.107
Sediment (marine water)	9.38E-3 mg/kg dw (EUSES 2.1.2)	0.107
Sewage Treatment Plant	0.045 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	0.013 mg/kg dw (EUSES 2.1.2)	0.086

2.3.4. Environmental release and exposure: IFRA SG-4; AISE SPERC 2.1.j.v2; Cosmetics Europe / AISE SPERC 2.3.a.v2; Cosmetics Europe SPERC 2.1.a.v2 (ERC 2)

Release route	Release rate	Release estimation method

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Water	0.042 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	2.27E-3 mg/L (EUSES 2.1.2)	0.052
Sediment (freshwater)	0.045 mg/kg dw (EUSES 2.1.2)	0.052
Marine water	2.26E-4 mg/L (EUSES 2.1.2)	0.051
Sediment (marine water)	4.53E-3 mg/kg dw (EUSES 2.1.2)	0.051
Sewage Treatment Plant	0.02 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	5.92E-3 mg/kg dw (EUSES 2.1.2)	0.039

2.3.5. Environmental release and exposure: IFRA SG-5; AISE SPERC 2.1.k.v2; Cosmetics Europe / AISE SPERC 2.3.b.v2; Cosmetics Europe SPERC 2.1.b.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.036 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	1.98E-3 mg/L (EUSES 2.1.2)	0.045
Sediment (freshwater)	0.04 mg/kg dw (EUSES 2.1.2)	0.045
Marine water	1.97E-4 mg/L (EUSES 2.1.2)	0.045
Sediment (marine water)	3.94E-3 mg/kg dw (EUSES 2.1.2)	0.045
Sewage Treatment Plant	0.017 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	5.08E-3 mg/kg dw (EUSES 2.1.2)	0.034

2.3.6. Environmental release and exposure: IFRA SG-6; AISE SPERC 2.1.i.v2; Cosmetics Europe / AISE SPERC 2.3.c.v2; Cosmetics Europe SPERC 2.1.c.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.072 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	3.73E-3 mg/L (EUSES 2.1.2)	0.085
Sediment (freshwater)	0.075 mg/kg dw (EUSES 2.1.2)	0.085
Marine water	3.72E-4 mg/L (EUSES 2.1.2)	0.085
Sediment (marine water)	7.44E-3 mg/kg dw (EUSES 2.1.2)	0.085
Sewage Treatment Plant	0.035 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	0.01 mg/kg dw (EUSES 2.1.2)	0.068

2.3.7. Environmental release and exposure: IFRA SG-7; Cosmetics Europe SPERC 2.2.a.v2; Cosmetics Europe SPERC 2.2.c.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0 kg/day	Estimated release factor

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	2.35E-4 mg/L (EUSES 2.1.2)	< 0.01
Sediment (freshwater)	4.69E-3 mg/kg dw (EUSES 2.1.2)	< 0.01
Marine water	2.23E-5 mg/L (EUSES 2.1.2)	< 0.01
Sediment (marine water)	4.47E-4 mg/kg dw (EUSES 2.1.2)	< 0.01
Sewage Treatment Plant	0 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	3.58E-5 mg/kg dw (EUSES 2.1.2)	< 0.01

2.3.8. Environmental release and exposure: IFRA SG-8; Cosmetics Europe SPERC 2.1.d.v2; Cosmetics Europe SPERC 2.1.j.v2 (ERC 2)

Release route	Release rate	Release estimation method
Water	0.12 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	6.06E-3 mg/L (EUSES 2.1.2)	0.138
Sediment (freshwater)	0.121 mg/kg dw (EUSES 2.1.2)	0.138
Marine water	6.05E-4 mg/L (EUSES 2.1.2)	0.138
Sediment (marine water)	0.012 mg/kg dw (EUSES 2.1.2)	0.138
Sewage Treatment Plant	0.058 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	0.017 mg/kg dw (EUSES 2.1.2)	0.112

2.3.9. Worker exposure: CS1; Transfer of substance or mixture (charging/discharging) at dedicated facilities; AISE M-6 (PROC 8b)

2.3.10. Worker exposure: CS2; Laboratory activities; Use as laboratory reagent; AISE M-9 (PROC 15)

2.3.11. Worker exposure: CS3; Storage; AISE M-1 (PROC 1)

2.3.12. Worker exposure: CS4; Mixing operations; Closed systems; Filling of articles/equipment; With sample collection; AISE M-3 (PROC 3)

2.3.13. Worker exposure: CS5; Mixing or blending in batch processes; Open systems; With sample collection; AISE M-5 (PROC 5)

2.3.14. Worker exposure: CS6; Equipment cleaning and maintenance (PROC 8a)

2.3.15. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC 2)

2.3.16. Worker exposure: CS7; Transfer of substance or mixture into small containers (dedicated filling line, including weighing); AISE M-7 (PROC 9)

2.3.17. Worker exposure: CS8; Tableting, compression, extrusion or pelletisation; AISE M-8

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

(PROC 14)

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures. Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

3. ES 3: Use at industrial sites; Washing and Cleaning Products

3.1. Title section

ES name: GES 3; Industrial end-use of washing and cleaning products
Product category: Washing and Cleaning Products (PC 35)

Environment

1: GES 3; Industrial end-use of washing and cleaning products	ERC 4
Worker	
2: Industrial use of food beverage and pharmaceutical products; CS13-u; Food process cleaner. Cleaning In place (CIP) process; AISE-P801; CS17-u; Defoaming product. Automatic process; AISE-P805	PROC 1
3: Industrial use of laundry products; CS1-u; Laundry detergent. Automatic process; AISE-P101; CS2-u; Conditioner (softner/starch). Automatic process; AISE-P104; CS3-u; Laundry aid (gasing). Automatic process; AISE-P107; CS4-u; Laundry aid (non-gasing). Automatic process; AISE-P110	PROC 2
4: Industrial use; Dedicated equipment; Pharmaceuticals; CS21-u; Disinfection product. Semi-automatic process; AISE-P810	PROC 4
5: Industrial use of vehicle cleaning products; CS5-u; Train cleaner. Semi-Automatic process; AISE-P707; CS6-u; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-u; Car wash product. Semi-Automatic process; AISE-P709; CS10-u; Dewaxing product. Semi-Automatic process; AISE-P712; CS14-u; Food process cleaner. Semi closed cleaning process; AISE-P802	PROC 4
6: Industrial use of water treatment products; CS24-u; Preservation and sanitation agent . Drink and pool water; AISE-P904; CS23-u; Sanitation agent. Waste water; AISE-P905	PROC 4
7: Industrial use of vehicle cleaning products; CS8-u; Car wash product. Spray and rinse process; AISE-P710	PROC 7
8: Industrial use of vehicle cleaning products; CS12-u1; Car wash product. Spray and wipe manual process; AISE-P711; CS9-u1; Boat cleaner. Spray and wipe manual process; AISE-P714	PROC 7
9: Industrial use of food beverage and pharmaceutical products; CS18-u; Foam cleaner. Semi-Automatic with venting process; AISE-P806	PROC 7
10: Industrial use of food beverage and pharmaceutical products; CS15-u; Chain maintenance product. Automatic spray process; AISE-P803; CS19-u; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-u; Animal housing care. Semi-Automatic process; AISE-P809; CS20-u; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811	PROC 7
11: Industrial use of façade/surface cleaning products; CS25-u; Façade/surface cleaner. High pressure process; AISE-P906; CS26-u; Façade/surface cleaner. Medium pressure process; AISE-P907	PROC 7
12: Industrial use of laundry products; CS1-p; Laundry detergent. Automatic process; AISE-P101; CS2-p; Conditioner (softner/starch). Automatic process; AISE-P104; CS3-p; Laundry aid (gasing). Automatic process; AISE-P107; CS4-p; Laundry aid (non-gasing). Automatic process; AISE-P110; CS13-p; Industrial use of food beverage and pharmaceutical products; AISE-P801; CS14-p; Food process cleaner. Cleaning In place (CIP) process; AISE-P802; CS15-p; Food process cleaner. Semi closed cleaning process; Chain maintenance product. Automatic spray process; AISE-P803; CS17-p; Defoaming product. Automatic process; AISE-P805	PROC 8b
13: Industrial use of water treatment products; CS23-p; Preservation and sanitation agent . Drink and pool water; AISE-P904; CS24-p; Sanitation agent. Waste water; AISE-P905; Industrial use of façade/surface cleaning products; CS25-p; Façade/surface cleaner. High pressure process; AISE-P906; CS26-p; Façade/surface cleaner. Medium pressure process; AISE-P907	PROC 8b
14: Industrial use of vehicle cleaning products; CS5-p; Train cleaner. Semi-Automatic process; AISE-P707; CS6-p; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-p; Car wash product. Semi-Automatic process; AISE-P709; CS8-p; Car wash product. Spray and rinse process; AISE-P710; CS10-p; Dewaxing product. Semi-	PROC 8b

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Automatic process; AISE-P712; Industrial use of food beverage and pharmaceutical products; CS19-p; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-p; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811
 15: Industrial use of vehicle cleaning products; CS9-p; Car wash product. Spray and wipe manual process; AISE- PROC 8b P711; CS11-p; Boat cleaner. Manual process; AISE-P713; CS12-p; Boat cleaner. Spray and wipe manual process; AISE-P714
 16: Industrial use of food beverage and pharmaceutical products; CS20-p; Animal housing care. Semi-Automatic PROC 8b process; AISE-P809; CS21-p; Disinfection product. Semi-automatic process; AISE-P810
 17: Industrial use of food beverage and pharmaceutical products; CS18-p; Foam cleaner. Semi-Automatic with PROC 8b venting process; AISE-P806
 18: Industrial use of vehicle cleaning products; CS9-u2; Car wash product. Spray and wipe manual process; AISE- PROC 10 P711; CS12-u2; Boat cleaner. Manual process; AISE-P713; CS11-u; Boat cleaner. Spray and wipe manual process; AISE-P714
 19: Industrial use of food beverage and pharmaceutical products; CS16-u; Chain maintenance product. Automatic PROC 13 drip and brush process; AISE-P804

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: GES 3; Industrial end-use of washing and cleaning products (ERC 4)

3.2.2. Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product (article) characteristics
Liquid
Covers concentrations up to 1 %
Technical and organisational conditions and measures
Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.; Ensure regular inspection, cleaning and maintenance of equipment and machines.; Clear spills immediately.; Ensure daily cleaning of the equipment.
Conditions and measures related to personal protection, hygiene and health evaluation
Use suitable eye protection.
Other conditions affecting workers exposure
Assumes process temperature up to 40 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Industrial use of food beverage and pharmaceutical products; CS13-u; Food process cleaner. Cleaning In place (CIP) process; AISE-P801; CS17-u; Defoaming product. Automatic process; AISE-P805 (PROC 1)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation; No. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; One hand face only (240 cm2) Indoor use
Industrial use of laundry products; CS1-u; Laundry detergent. Automatic process; AISE-P101; CS2-u; Conditioner (softener/starch). Automatic process; AISE-P104; CS3-u; Laundry aid (gasing). Automatic process; AISE-	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation; No. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>P107; CS4-u; Laundry aid (non-gasing). Automatic process; AISE-P110 (PROC 2)</p>	<p>also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use</p>
<p>Industrial use; Dedicated equipment; Pharmaceuticals; CS21-u; Disinfection product. Semi-automatic process; AISE-P810 (PROC 4)</p>	<p>Covers use up to 4 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90% Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use</p>
<p>Industrial use of vehicle cleaning products; CS5-u; Train cleaner. Semi-Automatic process; AISE-P707; CS6-u; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-u; Car wash product. Semi-Automatic process; AISE-P709; CS10-u; Dewaxing product. Semi-Automatic process; AISE-P712; CS14-u; Food process cleaner. Semi closed cleaning process; AISE-P802 (PROC 4)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands face only (480 cm2) Outdoor use</p>
<p>Industrial use of water treatment products; CS24-u; Preservation and sanitation agent. Drink and pool water; AISE-P904; CS23-u; Sanitation agent. Waste water; AISE-P905 (PROC 4)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands face only (480 cm2) Outdoor use</p>
<p>Industrial use of vehicle cleaning products; CS8-u; Car wash product. Spray and rinse process; AISE-P710 (PROC 7)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Industrial use of vehicle cleaning products; CS12-u1; Car wash product. Spray and wipe manual process; AISE-P711; CS9-u1; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 7)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Industrial use of food beverage and pharmaceutical products; CS18-u;</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour</p>

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>Foam cleaner. Semi-Automatic with venting process; AISE-P806 (PROC 7)</p>	<p>Provide enclosing hood with very high effectiveness (such as fume cupboard) or effective ventilation by spray booth according to EN 16985. Ensure effectiveness is at least 95%. Respiratory protection; No. Consumer protection; dermal; No. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Indoor use</p>
<p>Industrial use of food beverage and pharmaceutical products; CS15-u; Chain maintenance product. Automatic spray process; AISE-P803; CS19-u; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-u; Animal housing care. Semi-Automatic process; AISE-P809; CS20-u; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811 (PROC 7)</p>	<p>Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation; No. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Indoor use</p>
<p>Industrial use of façade/surface cleaning products; CS25-u; Façade/surface cleaner. High pressure process; AISE-P906; CS26-u; Façade/surface cleaner. Medium pressure process; AISE-P907 (PROC 7)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Industrial use of laundry products; CS1-p; Laundry detergent. Automatic process; AISE-P101; CS2-p; Conditioner (softner/starch). Automatic process; AISE-P104; CS3-p; Laundry aid (gasing). Automatic process; AISE-P107; CS4-p; Laundry aid (non-gasing). Automatic process; AISE-P110; CS13-p; Industrial use of food beverage and pharmaceutical products; AISE-P801; CS14-p; Food process cleaner. Cleaning In place (CIP) process; AISE-P802; CS15-p; Food process cleaner. Semi closed cleaning process; Chain maintenance product. Automatic spray process; AISE-P803; CS17-p; Defoaming product. Automatic process; AISE-P805 (PROC 8b)</p>	<p>Covers use up to 0.25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation; No. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Industrial use of water treatment products; CS23-p; Preservation and sanitation agent . Drink and pool water; AISE-P904; CS24-p; Sanitation agent. Waste water; AISE-P905; Industrial use of façade/surface cleaning products; CS25-p; Façade/surface cleaner. High pressure process; AISE-P906; CS26-p; Façade/surface cleaner. Medium pressure process; AISE-P907 (PROC 8b)</p>	<p>Covers use up to 0.25 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Industrial use of vehicle cleaning</p>	<p>Covers use up to 1 h/day</p>
<p>Administrative information: Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38 Sales & Distribution Information: VE01/FR/CH11/01 Shipping Order Information: 27 410 973/22 908 364</p>	

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

Givaudan

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>products; CS5-p; Train cleaner. Semi-Automatic process; AISE-P707; CS6-p; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-p; Car wash product. Semi-Automatic process; AISE-P709; CS8-p; Car wash product. Spray and rinse process; AISE-P710; CS10-p; Dewaxing product. Semi-Automatic process; AISE-P712; Industrial use of food beverage and pharmaceutical products; CS19-p; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-p; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811 (PROC 8b)</p>	<p>Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Industrial use of vehicle cleaning products; CS9-p; Car wash product. Spray and wipe manual process; AISE-P711; CS11-p; Boat cleaner. Manual process; AISE-P713; CS12-p; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 8b)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Industrial use of food beverage and pharmaceutical products; CS20-p; Animal housing care. Semi-Automatic process; AISE-P809; CS21-p; Disinfection product. Semi-automatic process; AISE-P810 (PROC 8b)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Industrial use of food beverage and pharmaceutical products; CS18-p; Foam cleaner. Semi-Automatic with venting process; AISE-P806 (PROC 8b)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Provide enclosing hood with very high effectiveness (such as fume cupboard) or effective ventilation by spray booth according to EN 16985. Ensure effectiveness is at least 95%. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Industrial use of vehicle cleaning products; CS9-u2; Car wash product. Spray and wipe manual process; AISE-P711; CS12-u2; Boat cleaner. Manual process; AISE-P713; CS11-u; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 10)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Industrial use of food beverage and pharmaceutical products; CS16-u; Chain maintenance product. Automatic</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or</p>
<p>Administrative information: Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38 Sales & Distribution Information: VE01/FR/CH11/01 Shipping Order Information: 27 410 973/22 908 364</p>	

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

drip and brush process; AISE-P804 (PROC 13)	enclosing hood type). Ensure effectiveness is at least 90% Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm ²) Indoor use
--	--

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: GES 3; Industrial end-use of washing and cleaning products (ERC 4)

Release route	Release rate	Release estimation method
Water	- kg/day	ERC
Air	- kg/day	ERC
Soil	- kg/day	ERC

3.3.2. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS13-u; Food process cleaner. Cleaning In place (CIP) process; AISE-P801; CS17-u; Defoaming product. Automatic process; AISE-P805 (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.18E-3 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, long term	4.18E-3 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Dermal, systemic, long term	3.4E-4 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	9.92E-5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	9.92E-5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.3. Worker exposure: Industrial use of laundry products; CS1-u; Laundry detergent. Automatic process; AISE-P101; CS2-u; Conditioner (softner/starch). Automatic process; AISE-P104; CS3-u; Laundry aid (gasing). Automatic process; AISE-P107; CS4-u; Laundry aid (non-gasing). Automatic process; AISE-P110 (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	1.671 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	1.671 mg/m ³ (TRA Workers 3.0)	< 0.01
Dermal, systemic, long term	0.014 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	2E-3 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	2E-3 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.4. Worker exposure: Industrial use; Dedicated equipment; Pharmaceuticals; CS21-u; Disinfection product. Semi-automatic process; AISE-P810 (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.179 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	1.194 mg/m ³ (TRA Workers 3.0)	0.017
Inhalation, local, long term	0.179 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	1.194 mg/m ³ (TRA Workers 3.0)	< 0.01

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Dermal, systemic, long term	0.069 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.5. Worker exposure: Industrial use of vehicle cleaning products; CS5-u; Train cleaner. Semi-Automatic process; AISE-P707; CS6-u; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-u; Car wash product. Semi-Automatic process; AISE-P709; CS10-u; Dewaxing product. Semi-Automatic process; AISE-P712; CS14-u; Food process cleaner. Semi closed cleaning process; AISE-P802 (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.069 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.033

3.3.6. Worker exposure: Industrial use of water treatment products; CS24-u; Preservation and sanitation agent . Drink and pool water; AISE-P904; CS23-u; Sanitation agent. Waste water; AISE-P905 (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.069 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.033

3.3.7. Worker exposure: Industrial use of vehicle cleaning products; CS8-u; Car wash product. Spray and rinse process; AISE-P710 (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.429 mg/kg bw/day (TRA Workers 3.0)	0.021
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.033

3.3.8. Worker exposure: Industrial use of vehicle cleaning products; CS12-u1; Car wash product. Spray and wipe manual process; AISE-P711; CS9-u1; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.429 mg/kg bw/day (TRA Workers 3.0)	0.021
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.033

3.3.9. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS18-u; Foam cleaner. Semi-Automatic with venting process; AISE-P806 (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.984 mg/m ³ (TRA Workers 3.0)	0.042
Inhalation, systemic, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.169
Inhalation, local, long term	2.984 mg/m ³ (TRA Workers 3.0)	0.017
Inhalation, local, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.068
Dermal, systemic, long term	4.286 mg/kg bw/day (TRA Workers 3.0)	0.214
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.257

3.3.10. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS15-u; Chain maintenance product. Automatic spray process; AISE-P803; CS19-u; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-u; Animal housing care. Semi-Automatic process; AISE-P809; CS20-u; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811 (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.429 mg/kg bw/day (TRA Workers 3.0)	0.021
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.081

3.3.11. Worker exposure: Industrial use of façade/surface cleaning products; CS25-u; Façade/surface cleaner. High pressure process; AISE-P906; CS26-u; Façade/surface cleaner. Medium pressure process; AISE-P907 (PROC 7)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.429 mg/kg bw/day (TRA Workers 3.0)	0.021
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.081

3.3.12. Worker exposure: Industrial use of laundry products; CS1-p; Laundry detergent. Automatic process; AISE-P101; CS2-p; Conditioner (softner/starch). Automatic process; AISE-P104; CS3-p; Laundry aid (gasing). Automatic process; AISE-P107; CS4-p; Laundry aid (non-gasing). Automatic process; AISE-P110; CS13-p; Industrial use of food beverage and pharmaceutical products; AISE-P801; CS14-p; Food process cleaner. Cleaning In place (CIP) process; AISE-P802; CS15-p; Food process cleaner. Semi closed cleaning process; Chain maintenance product. Automatic spray process; AISE-P803; CS17-p; Defoaming product. Automatic process; AISE-P805 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.209 mg/m ³ (TRA Workers 3.0)	< 0.01

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	0.209 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.13. Worker exposure: Industrial use of water treatment products; CS23-p; Preservation and sanitation agent . Drink and pool water; AISE-P904; CS24-p; Sanitation agent. Waste water; AISE-P905; Industrial use of façade/surface cleaning products; CS25-p; Façade/surface cleaner. High pressure process; AISE-P906; CS26-p; Façade/surface cleaner. Medium pressure process; AISE-P907 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.209 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	0.209 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.14. Worker exposure: Industrial use of vehicle cleaning products; CS5-p; Train cleaner. Semi-Automatic process; AISE-P707; CS6-p; Aeroplane cleaner. Semi-Automatic process; AISE-P708; CS7-p; Car wash product. Semi-Automatic process; AISE-P709; CS8-p; Car wash product. Spray and rinse process; AISE-P710; CS10-p; Dewaxing product. Semi-Automatic process; AISE-P712; Industrial use of food beverage and pharmaceutical products; CS19-p; Foam cleaner. Semi-Automatic without venting process; AISE-P807; CS22-p; Disinfection product. Fogging and gassing Semi-automatic process; AISE-P811 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.013

3.3.15. Worker exposure: Industrial use of vehicle cleaning products; CS9-p; Car wash product. Spray and wipe manual process; AISE-P711; CS11-p; Boat cleaner. Manual process; AISE-P713; CS12-p; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.013

3.3.16. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS20-

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

p; Animal housing care. Semi-Automatic process; AISE-P809; CS21-p; Disinfection product. Semi-automatic process; AISE-P810 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.169
Inhalation, local, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	11.93 mg/m ³ (TRA Workers 3.0)	0.068
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.015

3.3.17. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS18-p; Foam cleaner. Semi-Automatic with venting process; AISE-P806 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.03 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, long term	0.03 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

3.3.18. Worker exposure: Industrial use of vehicle cleaning products; CS9-u2; Car wash product. Spray and wipe manual process; AISE-P711; CS12-u2; Boat cleaner. Manual process; AISE-P713; CS11-u; Boat cleaner. Spray and wipe manual process; AISE-P714 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.014
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.073

3.3.19. Worker exposure: Industrial use of food beverage and pharmaceutical products; CS16-u; Chain maintenance product. Automatic drip and brush process; AISE-P804 (PROC 13)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	2.387 mg/m ³ (TRA Workers 3.0)	0.034
Inhalation, local, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	2.387 mg/m ³ (TRA Workers 3.0)	0.014
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.015

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses for environmental exposure is covered under GES6. ERC4 is covered under ERC8. In accordance with IFRA REACH Exposure Scenarios for Fragrance Substances Version 2.1, 11th December 2012), the total tonnage under ERC4 can be considered under ERC8. This approach can be justified since the total volume for fragrance substances that is applied for industrial use is only a fraction of the volumes going to consumer and professional uses. Also the industrial end-use products are similar to those used by professionals and consumers and release will be to the waste water stream. In industrial settings normally additional RMMs are available in the form of on-site industrial sewage treatment plants. Therefore this approach can be considered as a worst case approach as only the municipal treatment plant is

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

considered in wide-dispersive uses.

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

4. ES 4: Widespread use by professional workers; Washing and Cleaning Products

4.1. Title section

ES name: GES 4; Professional end-use of washing and cleaning products

Product category: Washing and Cleaning Products (PC 35)

Environment

1: GES 4; Professional end-use of washing and cleaning products	ERC 8a
Worker	
2: Professional use of laundry products; CS1-u; Laundry detergent. Semi automatic process; AISE-P102; CS3-u; Conditioner (softner/starch). Semi automatic process; AISE-P105; CS4-u; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-u; Laundry aid (non-gasing). Semi automatic process; AISE-P111; Professional use of dishwashing products; CS10-u; Dishwash product. Semi-Automatic process; AISE-P203; CS11-u; Rinse aid. Automatic process; AISE-P204; Professional use of medical devices; CS48-u; Medical devices . Semi-automatic process; AISE-P1101	PROC 1
3: Professional use of dishwashing products; CS9-u; Dishwash product. Automatic process; AISE-P202	PROC 2
4: Professional use of laundry products; CS6-u; Laundry aid (non-gasing). Manual process; AISE-P112	PROC 4
5: Professional use of vehicle cleaning products; Semi-automated task; CS39-u; Car wash product. Semi-Automatic process; AISE-P701; CS42-u; Dewaxing product. Semi-Automatic process; AISE-P704	PROC 4
6: Professional use of laundry products; CS1-p; Laundry detergent. Semi automatic process; AISE-P102; CS3-p; Conditioner (softner/starch). Semi automatic process; AISE-P105; CS4-p; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-p; Laundry aid (non-gasing). Semi automatic process; AISE-P111; CS6-p; Laundry aid (non-gasing). Manual process; AISE-P112; Professional use of dishwashing products; CS10-p; Dishwash product. Semi-Automatic process; AISE-P201; CS11-p; Rinse aid. Automatic process; AISE-P204; Professional use of general surface cleaning products; CS20-p; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices; CS48-p; Medical devices . Semi-automatic process; AISE-P1101; CS49-p; Medical devices . Dipping process; AISE-P1102	PROC 8a
7: Professional use of façade/surface cleaning products; CS46-p; Façade/surface cleaner. High pressure process; AISE-P901; CS47-p; Façade/surface cleaner. Medium pressure process; AISE-P902	PROC 8a
8: Professional use of dishwashing products; CS8-p; Dishwash product. Manual process; AISE-P201	PROC 8a
9: Professional use of floor care products; CS31-p; Floor cleaner. Manual process; AISE-P403; CS29-p; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-p; Floor cleaner. Spray and wipe manual process; AISE-P402; CS34-p; Carpet cleaner. Manual process; AISE-P409; CS35-p; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use of general surface cleaning products; CS12-p; General purpose cleaner. Manual process; AISE-P301; CS13-p; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-p; Kitchen cleaner. Manual process; AISE-P303; CS15-p; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS16-p; Sanitary cleaner. Manual process; AISE-P305; CS17-p; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-p; Glass cleaner. Manual process; AISE-P312; Professional use; Pharmaceuticals; CS45-p; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS51-p; Medical devices . Spray process; AISE-P1104	PROC 8a
10: Professional use of vehicle cleaning products; CS39-p; Car wash product. Semi-Automatic process; AISE-P701; CS40-p; Car wash product. Spray and wipe manual process; AISE-P702; CS42-p; Dewaxing product. Semi-Automatic process; AISE-P704; Professional use of laundry products; CS2-p; Laundry detergent. Manual process; AISE-P103; Professional use of general surface cleaning products; CS19-p; Descaling agent. Spray and rinse manual process; AISE-P308; CS25-p; Surface disinfectant. Manual process; AISE-P314; CS26-p; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS32-p; Floor stripper. Manual process; AISE-P404; CS33-p; Floor stripper. Semi-Automatic process; AISE-P405; Professional use of medical devices; CS50-p; Medical devices . Manual process; AISE-P1103	PROC 8a

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

11: Professional use of vehicle cleaning products; CS41-p; Car wash product. Spray and wipe manual process; AISE-P703; CS43-p; Boat cleaner. Manual process; AISE-P705; CS44-p; Boat cleaner. Spray and wipe manual process; AISE-P706	PROC 8a
12: Professional use of dishwashing products; CS9-p; Dishwash product. Automatic process; AISE-P202	PROC 8b
13: Professional use of general surface cleaning products; CS21-u; Oven/Grill Cleaner. Manual process; AISE-P301	PROC 10
14: Professional use of laundry products; CS2-u; Laundry detergent. Manual process; AISE-P103; Professional use of dishwashing products; CS8-u; Dishwash product. Manual process; AISE-P201; Professional use of general surface cleaning products; CS28-u; Wet wipe. Manual process; AISE-P317; Professional use of floor care products; CS36-u1; Carpet cleaner. Spray and brush manual process; AISE-P411	PROC 10
15: Professional use of general surface cleaning products; CS18-u; Descaling agent. Manual process; AISE-P307	PROC 10
16: Professional use of floor care products; CS31-u; Floor cleaner. Manual process; AISE-P403; Professional use of laundry products; CS7-u1; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS12-u; General purpose cleaner. Manual process; AISE-P301; CS13-u1; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-u; Kitchen cleaner. Manual process; AISE-P303; CS15-u1; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS16-u; Sanitary cleaner. Manual process; AISE-P305; CS17-u1; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-u; Glass cleaner. Manual process; AISE-P312; CS24-u1; Glass cleaner. Spray and wipe manual process; AISE-P313; CS25-u; Surface disinfectant. Manual process; AISE-P314; CS26-u1; Surface disinfectant. Spray and rinse manual process; AISE-P315; CS27-u; Metal cleaning agent. Manual process; AISE-P316; CS29-u; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-u1; Floor cleaner. Spray and wipe manual process; AISE-P402; CS33-u; Floor stripper. Semi-Automatic process; AISE-P405; CS34-u; Carpet cleaner. Manual process; AISE-P409; CS35-u; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use; Pharmaceuticals; CS45-u; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS50-u; Medical devices . Manual process; AISE-P1103; CS51-u1; Medical devices . Spray process; AISE-P1104	PROC 10
17: Professional use of general surface cleaning products; CS19-u1; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u1; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311; Professional use of floor care products; CS32-u; Floor stripper. Manual process; AISE-P404	PROC 10
18: Professional use of vehicle cleaning products; CS41-u1; Car wash product. Spray and wipe manual process; AISE-P703; CS43-u; Boat cleaner. Manual process; AISE-P705; CS44-u1; Boat cleaner. Spray and wipe manual process; AISE-P706	PROC 10
19: Professional use of façade/surface cleaning products; CS47-u1; Façade/surface cleaner. Medium pressure process; AISE-P902	PROC 10
20: Professional use of vehicle cleaning products; CS40-u; Car wash product. Spray and rinse process; AISE-P702; Professional use of laundry products; CS7-u2; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS13-u2; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS15-u2; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS17-u2; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS24-u2; Glass cleaner. Spray and wipe manual process; AISE-P313; CS26-u2; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS30-u2; Floor cleaner. Spray and wipe manual process; AISE-P402; CS36-u2; Carpet cleaner. Spray and brush manual process; AISE-P411; Professional use of medical devices; CS51-u2; Medical devices . Spray process; AISE-P1104	PROC 11
21: Professional use of general surface cleaning products; CS19-u2; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u2; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311	PROC 11
22: Professional use of vehicle cleaning products; CS41-u2; Car wash product. Spray and wipe manual process; AISE-P703; CS44-u2; Boat cleaner. Spray and wipe manual process; AISE-P706	PROC 11
23: Professional use of façade/surface cleaning products; CS47-u2; Façade/surface cleaner. Medium pressure process; AISE-P902	PROC 11
24: Professional use of façade/surface cleaning products; CS46-u; Façade/surface cleaner. High pressure process; AISE-P901	PROC 11
25: Professional use of maintenance products; CS37; Drain unblocker. Manual process; AISE-P606; CS38; Drain cleaner. Manual process; AISE-P607	PROC 13
26: Professional use of general surface cleaning products; CS20-u; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices; CS49-u; Medical devices . Dipping process; AISE-P1102	PROC 13

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: GES 4; Professional end-use of washing and cleaning products (ERC 8a)

Amount used, frequency and duration of use (or from service life)

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Daily local widespread use amount; <=; 0; tonnes/day

4.2.2. Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product (article) characteristics

Liquid

Covers concentrations up to 1 %

Technical and organisational conditions and measures

Occupational Health and Safety Management System; Basic

Local exhaust ventilation; No.

Other conditions affecting workers exposure

Assumes process temperature up to 40 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Professional use of laundry products; CS1-u; Laundry detergent. Semi automatic process; AISE-P102; CS3-u; Conditioner (softner/starch). Semi automatic process; AISE-P105; CS4-u; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-u; Laundry aid (non-gasing). Semi automatic process; AISE-P111; Professional use of dishwashing products; CS10-u; Dishwash product. Semi-Automatic process; AISE-P203; CS11-u; Rinse aid. Automatic process; AISE-P204; Professional use of medical devices; CS48-u; Medical devices . Semi-automatic process; AISE-P1101 (PROC 1)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Consumer protection; dermal; No. Covers skin contact area up to ; One hand face only (240 cm2) Indoor use
Professional use of dishwashing products; CS9-u; Dishwash product. Automatic process; AISE-P202 (PROC 2)	Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use
Professional use of laundry products; CS6-u; Laundry aid (non-gasing). Manual process; AISE-P112 (PROC 4)	Covers use up to 0,25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use
Professional use of vehicle cleaning products; Semi-automated task; CS39-u; Car wash product. Semi-Automatic process; AISE-P701; CS42-u; Dewaxing product. Semi-Automatic process;	Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Respiratory protection; No. Use suitable eye protection.

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>AISE-P704 (PROC 4)</p>	<p>Covers skin contact area up to ; Two hands face only (480 cm2) Outdoor use</p>
<p>Professional use of laundry products; CS1-p; Laundry detergent. Semi automatic process; AISE-P102; CS3-p; Conditioner (softner/starch). Semi automatic process; AISE-P105; CS4-p; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-p; Laundry aid (non-gasing). Semi automatic process; AISE-P111; CS6-p; Laundry aid (non-gasing). Manual process; AISE-P112; Professional use of dishwashing products; CS10-p; Dishwash product. Semi-Automatic process; AISE-P201; CS11-p; Rinse aid. Automatic process; AISE-P204; Professional use of general surface cleaning products; CS20-p; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices; CS48-p; Medical devices . Semi-automatic process; AISE-P1101; CS49-p; Medical devices . Dipping process; AISE-P1102 (PROC 8a)</p>	<p>Covers use up to 0.25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Professional use of façade/surface cleaning products; CS46-p; Façade/surface cleaner. High pressure process; AISE-P901; CS47-p; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 8a)</p>	<p>Covers use up to 0.25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Professional use of dishwashing products; CS8-p; Dishwash product. Manual process; AISE-P201 (PROC 8a)</p>	<p>Covers use up to 0.25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Professional use of floor care products; CS31-p; Floor cleaner. Manual process; AISE-P403; CS29-p; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-p; Floor cleaner. Spray and wipe manual process; AISE-P402; CS34-p; Carpet cleaner. Manual process; AISE-P409; CS35-p; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use of general surface cleaning products; CS12-p; General purpose cleaner. Manual process; AISE-P301; CS13-p; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-p; Kitchen cleaner. Manual process; AISE-P303; CS15-p; Kitchen cleaner. Spray and wipe manual process; AISE-P304;</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Respiratory protection; No. Use suitable eye protection. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Administrative information: Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38 Sales & Distribution Information: VE01/FR/CH11/01 Shipping Order Information: 27 410 973/22 908 364</p>	

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>CS16-p; Sanitary cleaner. Manual process; AISE-P305; CS17-p; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-p; Glass cleaner. Manual process; AISE-P312; Professional use; Pharmaceuticals; CS45-p; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS51-p; Medical devices . Spray process; AISE-P1104 (PROC 8a)</p>	
<p>Professional use of vehicle cleaning products; CS39-p; Car wash product. Semi-Automatic process; AISE-P701; CS40-p; Car wash product. Spray and wipe manual process; AISE-P702; CS42-p; Dewaxing product. Semi-Automatic process; AISE-P704; Professional use of laundry products; CS2-p; Laundry detergent. Manual process; AISE-P103; Professional use of general surface cleaning products; CS19-p; Descaling agent. Spray and rinse manual process; AISE-P308; CS25-p; Surface disinfectant. Manual process; AISE-P314; CS26-p; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS32-p; Floor stripper. Manual process; AISE-P404; CS33-p; Floor stripper. Semi-Automatic process; AISE-P405; Professional use of medical devices; CS50-p; Medical devices . Manual process; AISE-P1103 (PROC 8a)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Face/eye protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Professional use of vehicle cleaning products; CS41-p; Car wash product. Spray and wipe manual process; AISE-P703; CS43-p; Boat cleaner. Manual process; AISE-P705; CS44-p; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 8a)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No. Use suitable eye protection. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Professional use of dishwashing products; CS9-p; Dishwash product. Automatic process; AISE-P202 (PROC 8b)</p>	<p>Covers use up to 0.25 h/day Room ventilation; Basic; Up to 3 air change per hour Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Professional use of general surface cleaning products; CS21-u; Oven/Grill Cleaner. Manual process; AISE-P301</p>	<p>Covers use up to 1 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection.</p>

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

(PROC 10)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use
Professional use of laundry products; CS2-u; Laundry detergent. Manual process; AISE-P103; Professional use of dishwashing products; CS8-u; Dishwash product. Manual process; AISE-P201; Professional use of general surface cleaning products; CS28-u; Wet wipe. Manual process; AISE-P317; Professional use of floor care products; CS36-u1; Carpet cleaner. Spray and brush manual process; AISE-P411 (PROC 10)	Covers use up to 4 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands (960 cm2) Indoor use
Professional use of general surface cleaning products; CS18-u; Descaling agent. Manual process; AISE-P307 (PROC 10)	Covers use up to 4 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to Indoor use
Professional use of floor care products; CS31-u; Floor cleaner. Manual process; AISE-P403; Professional use of laundry products; CS7-u1; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS12-u; General purpose cleaner. Manual process; AISE-P301; CS13-u1; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-u; Kitchen cleaner. Manual process; AISE-P303; CS15-u1; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS16-u; Sanitary cleaner. Manual process; AISE-P305; CS17-u1; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-u; Glass cleaner. Manual process; AISE-P312; CS24-u1; Glass cleaner. Spray and wipe manual process; AISE-P313; CS25-u; Surface disinfectant. Manual process; AISE-P314; CS26-u1; Surface disinfectant. Spray and rinse manual process; AISE-P315; CS27-u; Metal cleaning agent. Manual process; AISE-P316; CS29-u; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-u1; Floor cleaner. Spray and wipe manual process; AISE-P402; CS33-u; Floor stripper. Semi-Automatic process; AISE-P405; CS34-u; Carpet	Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Respiratory protection; No. Face/eye protection; No. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>cleaner. Manual process; AISE-P409; CS35-u; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use; Pharmaceuticals; CS45-u; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS50-u; Medical devices. Manual process; AISE-P1103; CS51-u1; Medical devices. Spray process; AISE-P1104 (PROC 10)</p>	
<p>Professional use of general surface cleaning products; CS19-u1; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u1; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311; Professional use of floor care products; CS32-u; Floor stripper. Manual process; AISE-P404 (PROC 10)</p>	<p>Covers use up to 8 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2) Indoor use</p>
<p>Professional use of vehicle cleaning products; CS41-u1; Car wash product. Spray and wipe manual process; AISE-P703; CS43-u; Boat cleaner. Manual process; AISE-P705; CS44-u1; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 10)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Respiratory protection; No. Use suitable eye protection. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Professional use of façade/surface cleaning products; CS47-u1; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 10)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Covers skin contact area up to ; Two hands (960 cm2) Outdoor use</p>
<p>Professional use of vehicle cleaning products; CS40-u; Car wash product. Spray and rinse process; AISE-P702; Professional use of laundry products; CS7-u2; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS13-u2; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS15-u2; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS17-u2; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS24-u2; Glass cleaner. Spray and wipe manual process; AISE-P313; CS26-u2; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS30-u2; Floor cleaner. Spray and wipe manual process; AISE-P402; CS36-u2; Carpet</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Administrative information: Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38 Sales & Distribution Information: VE01/FR/CH11/01 Shipping Order Information: 27 410 973/22 908 364</p>	

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

<p>cleaner. Spray and brush manual process; AISE-P411; Professional use of medical devices; CS51-u2; Medical devices . Spray process; AISE-P1104 (PROC 11)</p>	
<p>Professional use of general surface cleaning products; CS19-u2; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u2; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311 (PROC 11)</p>	<p>Covers use up to 1 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Indoor use</p>
<p>Professional use of vehicle cleaning products; CS41-u2; Car wash product. Spray and wipe manual process; AISE-P703; CS44-u2; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 11)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Consumer protection; dermal; No. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Professional use of façade/surface cleaning products; CS47-u2; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 11)</p>	<p>Covers use up to 1 h/day Room ventilation; Basic; Up to 3 air change per hour Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Professional use of façade/surface cleaning products; CS46-u; Façade/surface cleaner. High pressure process; AISE-P901 (PROC 11)</p>	<p>Covers use up to 8 h/day Room ventilation; Basic; Up to 3 air change per hour Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Use suitable eye protection. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2) Outdoor use</p>
<p>Professional use of maintenance products; CS37; Drain unblocker. Manual process; AISE-P606; CS38; Drain cleaner. Manual process; AISE-P607 (PROC 13)</p>	<p>Covers use up to 0.25 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use</p>
<p>Professional use of general surface cleaning products; CS20-u; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices;</p>	<p>Covers use up to 1 h/day Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Respiratory protection; No. Use suitable eye protection.</p>
<p>Administrative information: Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38 Sales & Distribution Information: VE01/FR/CH11/01 Shipping Order Information: 27 410 973/22 908 364</p>	

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

CS49-u; Medical devices . Dipping process; AISE-P1102 (PROC 13)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands face only (480 cm2) Indoor use
--	--

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: GES 4; Professional end-use of washing and cleaning products (ERC 8a)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

4.3.2. Worker exposure: Professional use of laundry products; CS1-u; Laundry detergent. Semi automatic process; AISE-P102; CS3-u; Conditioner (softner/starch). Semi automatic process; AISE-P105; CS4-u; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-u; Laundry aid (non-gasing). Semi automatic process; AISE-P111; Professional use of dishwashing products; CS10-u; Dishwash product. Semi-Automatic process; AISE-P203; CS11-u; Rinse aid. Automatic process; AISE-P204; Professional use of medical devices; CS48-u; Medical devices . Semi-automatic process; AISE-P1101 (PROC 1)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.18E-3 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, long term	4.18E-3 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	0.017 mg/m ³ (TRA Workers 3.0)	< 0.01
Dermal, systemic, long term	3.4E-3 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	9.92E-4 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	9.92E-4 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

4.3.3. Worker exposure: Professional use of dishwashing products; CS9-u; Dishwash product. Automatic process; AISE-P202 (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.036

4.3.4. Worker exposure: Professional use of laundry products; CS6-u; Laundry aid (non-gasing). Manual process; AISE-P112 (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Dermal, systemic, long term	0.069 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.01 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		< 0.01

4.3.5. Worker exposure: Professional use of vehicle cleaning products; Semi-automated task; CS39-u; Car wash product. Semi-Automatic process; AISE-P701; CS42-u; Dewaxing product. Semi-Automatic process; AISE-P704 (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.686 mg/kg bw/day (TRA Workers 3.0)	0.034
Dermal, local, long term	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.094

4.3.6. Worker exposure: Professional use of laundry products; CS1-p; Laundry detergent. Semi automatic process; AISE-P102; CS3-p; Conditioner (softener/starch). Semi automatic process; AISE-P105; CS4-p; Laundry aid (gasing). Semi automatic process; AISE-P108; CS5-p; Laundry aid (non-gasing). Semi automatic process; AISE-P111; CS6-p; Laundry aid (non-gasing). Manual process; AISE-P112; Professional use of dishwashing products; CS10-p; Dishwash product. Semi-Automatic process; AISE-P201; CS11-p; Rinse aid. Automatic process; AISE-P204; Professional use of general surface cleaning products; CS20-p; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices; CS48-p; Medical devices . Semi-automatic process; AISE-P1101; CS49-p; Medical devices . Dipping process; AISE-P1102 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.044 mg/m ³ (TRA Workers 3.0)	0.015
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	1.044 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.022

4.3.7. Worker exposure: Professional use of façade/surface cleaning products; CS46-p; Façade/surface cleaner. High pressure process; AISE-P901; CS47-p; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.044 mg/m ³ (TRA Workers 3.0)	0.015
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	1.044 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.022

4.3.8. Worker exposure: Professional use of dishwashing products; CS8-p; Dishwash product. Manual process; AISE-P201 (PROC 8a)

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.044 mg/m ³ (TRA Workers 3.0)	0.015
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	1.044 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	1.371 mg/kg bw/day (TRA Workers 3.0)	0.069
Dermal, local, long term	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.083

4.3.9. Worker exposure: Professional use of floor care products; CS31-p; Floor cleaner. Manual process; AISE-P403; CS29-p; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-p; Floor cleaner. Spray and wipe manual process; AISE-P402; CS34-p; Carpet cleaner. Manual process; AISE-P409; CS35-p; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use of general surface cleaning products; CS12-p; General purpose cleaner. Manual process; AISE-P301; CS13-p; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-p; Kitchen cleaner. Manual process; AISE-P303; CS15-p; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS16-p; Sanitary cleaner. Manual process; AISE-P305; CS17-p; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-p; Glass cleaner. Manual process; AISE-P312; Professional use; Pharmaceuticals; CS45-p; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS51-p; Medical devices . Spray process; AISE-P1104 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	1.371 mg/kg bw/day (TRA Workers 3.0)	0.069
Dermal, local, long term	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.1 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.098

4.3.10. Worker exposure: Professional use of vehicle cleaning products; CS39-p; Car wash product. Semi-Automatic process; AISE-P701; CS40-p; Car wash product. Spray and wipe manual process; AISE-P702; CS42-p; Dewaxing product. Semi-Automatic process; AISE-P704; Professional use of laundry products; CS2-p; Laundry detergent. Manual process; AISE-P103; Professional use of general surface cleaning products; CS19-p; Descaling agent. Spray and rinse manual process; AISE-P308; CS25-p; Surface disinfectant. Manual process; AISE-P314; CS26-p; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS32-p; Floor stripper. Manual process; AISE-P404; CS33-p; Floor stripper. Semi-Automatic process; AISE-P405; Professional use of medical devices; CS50-p; Medical devices . Manual process; AISE-P1103 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.036

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

4.3.11. Worker exposure: Professional use of vehicle cleaning products; CS41-p; Car wash product. Spray and wipe manual process; AISE-P703; CS43-p; Boat cleaner. Manual process; AISE-P705; CS44-p; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 8a)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.036

4.3.12. Worker exposure: Professional use of dishwashing products; CS9-p; Dishwash product. Automatic process; AISE-P202 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	23.87 mg/m ³ (TRA Workers 3.0)	0.338
Inhalation, local, long term	0.597 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	23.87 mg/m ³ (TRA Workers 3.0)	0.135
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.015

4.3.13. Worker exposure: Professional use of general surface cleaning products; CS21-u; Oven/Grill Cleaner. Manual process; AISE-P301 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.014
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.043

4.3.14. Worker exposure: Professional use of laundry products; CS2-u; Laundry detergent. Manual process; AISE-P103; Professional use of dishwashing products; CS8-u; Dishwash product. Manual process; AISE-P201; Professional use of general surface cleaning products; CS28-u; Wet wipe. Manual process; AISE-P317; Professional use of floor care products; CS36-u1; Carpet cleaner. Spray and brush manual process; AISE-P411 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.089
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.036
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	2.743 mg/kg bw/day (TRA Workers 3.0)	0.137
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.226

4.3.15. Worker exposure: Professional use of general surface cleaning products; CS18-u; Descaling agent. Manual process; AISE-P307 (PROC 10)

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.089
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.036
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.014
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.103

4.3.16. Worker exposure: Professional use of floor care products; CS31-u; Floor cleaner. Manual process; AISE-P403; Professional use of laundry products; CS7-u1; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS12-u; General purpose cleaner. Manual process; AISE-P301; CS13-u1; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS14-u; Kitchen cleaner. Manual process; AISE-P303; CS15-u1; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS16-u; Sanitary cleaner. Manual process; AISE-P305; CS17-u1; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS23-u; Glass cleaner. Manual process; AISE-P312; CS24-u1; Glass cleaner. Spray and wipe manual process; AISE-P313; CS25-u; Surface disinfectant. Manual process; AISE-P314; CS26-u1; Surface disinfectant. Spray and rinse manual process; AISE-P315; CS27-u; Metal cleaning agent. Manual process; AISE-P316; CS29-u; Floor cleaner. Semi-Automatic process; AISE-P401; CS30-u1; Floor cleaner. Spray and wipe manual process; AISE-P402; CS33-u; Floor stripper. Semi-Automatic process; AISE-P405; CS34-u; Carpet cleaner. Manual process; AISE-P409; CS35-u; Carpet cleaner. Semi-Automatic process; AISE-P410; Professional use; Pharmaceuticals; CS45-u; Animal housing care. Manual process; AISE-P808; Professional use of medical devices; CS50-u; Medical devices . Manual process; AISE-P1103; CS51-u1; Medical devices . Spray process; AISE-P1104 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.148
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	2.743 mg/kg bw/day (TRA Workers 3.0)	0.137
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.285

4.3.17. Worker exposure: Professional use of general surface cleaning products; CS19-u1; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u1; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311; Professional use of floor care products; CS32-u; Floor stripper. Manual process; AISE-P404 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.148
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.014
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.162

4.3.18. Worker exposure: Professional use of vehicle cleaning products; CS41-u1; Car wash

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

product. Spray and wipe manual process; AISE-P703; CS43-u; Boat cleaner. Manual process; AISE-P705; CS44-u1; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.148
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	2.743 mg/kg bw/day (TRA Workers 3.0)	0.137
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.285

4.3.19. Worker exposure: Professional use of façade/surface cleaning products; CS47-u1; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	1.044 mg/m ³ (TRA Workers 3.0)	0.015
Inhalation, systemic, acute	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, local, long term	1.044 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.014
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.029

4.3.20. Worker exposure: Professional use of vehicle cleaning products; CS40-u; Car wash product. Spray and rinse process; AISE-P702; Professional use of laundry products; CS7-u2; Prespotter/Stain remover. Manual process; AISE-P113; Professional use of general surface cleaning products; CS13-u2; General purpose cleaner. Spray and wipe manual process; AISE-P302; CS15-u2; Kitchen cleaner. Spray and wipe manual process; AISE-P304; CS17-u2; Sanitary cleaner. Spray and wipe manual process; AISE-P306; CS24-u2; Glass cleaner. Spray and wipe manual process; AISE-P313; CS26-u2; Surface disinfectant. Spray and rinse manual process; AISE-P315; Professional use of floor care products; CS30-u2; Floor cleaner. Spray and wipe manual process; AISE-P402; CS36-u2; Carpet cleaner. Spray and brush manual process; AISE-P411; Professional use of medical devices; CS51-u2; Medical devices . Spray process; AISE-P1104 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	10.71 mg/kg bw/day (TRA Workers 3.0)	0.536
Dermal, local, long term	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.548

4.3.21. Worker exposure: Professional use of general surface cleaning products; CS19-u2; Descaling agent. Spray and rinse manual process; AISE-P308; CS22-u2; Oven/Grill Cleaner. Spray and wipe manual process; AISE-P311 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Dermal, systemic, long term	1.071 mg/kg bw/day (TRA Workers 3.0)	0.054
Dermal, local, long term	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.065

4.3.22. Worker exposure: Professional use of vehicle cleaning products; CS41-u2; Car wash product. Spray and wipe manual process; AISE-P703; CS44-u2; Boat cleaner. Spray and wipe manual process; AISE-P706 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	10.71 mg/kg bw/day (TRA Workers 3.0)	0.536
Dermal, local, long term	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.548

4.3.23. Worker exposure: Professional use of façade/surface cleaning products; CS47-u2; Façade/surface cleaner. Medium pressure process; AISE-P902 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	1.071 mg/kg bw/day (TRA Workers 3.0)	0.054
Dermal, local, long term	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.065

4.3.24. Worker exposure: Professional use of façade/surface cleaning products; CS46-u; Façade/surface cleaner. High pressure process; AISE-P901 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	4.177 mg/m ³ (TRA Workers 3.0)	0.024
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	1.071 mg/kg bw/day (TRA Workers 3.0)	0.054
Dermal, local, long term	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.05 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.113

4.3.25. Worker exposure: Professional use of maintenance products; CS37; Drain unblocker. Manual process; AISE-P606; CS38; Drain cleaner. Manual process; AISE-P607 (PROC 13)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.013

4.3.26. Worker exposure: Professional use of general surface cleaning products; CS20-u; Descaling agent. Dipping process; AISE-P309; Professional use of medical devices; CS49-u;

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Medical devices . Dipping process; AISE-P1102 (PROC 13)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.019

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures,

Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

5. ES 5: Widespread use by professional workers; Polishes and Wax Blends

5.1. Title section

ES name: GES 5; Professional end-use of polishes and wax blends

Product category: Polishes and Wax Blends (PC 31)

Environment	
1: GES 5; Professional end-use of polishes and wax blends	ERC 8a
Worker	
2: Professional use of maintenance products; CS8-u; Leather care product. Automatic process; AISE-P605	PROC 2
3: Professional use of maintenance products; CS8-p; Leather care product. Automatic process; AISE-P605	PROC 8b
4: Professional use of maintenance products; CS4-u; Furniture care product. Manual process; AISE-P601; Furniture care product. Spray and wipe manual process; AISE-P602; CS6-u; Leather care product. Manual process; AISE-P603; CS7-u1; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609	PROC 10
5: Professional use of floor care products; CS1-u; Polish / impregnating agent. Manual process; AISE-P406; Polish / impregnating agent. Semi-Automatic process; AISE-P407; CS3-u1; Polish / impregnating agent. Spray and wipe manual process; AISE-P408; Professional use of maintenance products; CS9-u; Stainless steel care. Manual process; AISE-P608	PROC 10
6: Professional use of maintenance products; CS5-u2; Furniture care product. Spray and wipe manual process; AISE-P602; CS7-u2; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609	PROC 11
7: Professional use of maintenance products; CS3-u2; Polish / impregnating agent. Spray and wipe manual process; AISE-P408	PROC 11
8: Professional uses; Mixing or blending in batch processes; Uses in cosmetics/personal care products, perfumes and fragrances	PROC 5
9: Professional uses; Transfer of substance or mixture (charging/discharging) at non dedicated-facilities; Uses in cosmetics/personal care products, perfumes and fragrances	PROC 8a

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: GES 5; Professional end-use of polishes and wax blends (ERC 8a)

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Amount used, frequency and duration of use (or from service life)

Daily local widespread use amount; <=; 0; tonnes/day

5.2.2. Control of worker exposure

Conditions of use applicable to all contributing scenarios

Product (article) characteristics

Liquid

Covers concentrations up to 1 %

Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Occupational Health and Safety Management System; Basic

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection.

Other conditions affecting workers exposure

Indoor use

Assumes process temperature up to 40 °C

Specific conditions of use per contributing scenario

Contributing scenario	Specific conditions of use
Professional use of maintenance products; CS8-u; Leather care product. Automatic process; AISE-P605 (PROC 2)	Covers use up to 8 h/day Local exhaust ventilation; No. Respiratory protection; No. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands face only (480 cm2)
Professional use of maintenance products; CS8-p; Leather care product. Automatic process; AISE-P605 (PROC 8b)	Covers use up to 1 h/day Local exhaust ventilation; No. Respiratory protection; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Covers skin contact area up to ; Two hands (960 cm2)
Professional use of maintenance products; CS4-u; Furniture care product. Manual process; AISE-P601; Furniture care product. Spray and wipe manual process; AISE-P602; CS6-u; Leather care product. Manual process; AISE-P603; CS7-u1; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609 (PROC 10)	Covers use up to 4 h/day Local exhaust ventilation; No. Respiratory protection; No. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands (960 cm2)
Professional use of floor care products; CS1-u; Polish / impregnating agent. Manual process; AISE-P406; Polish / impregnating agent. Semi-Automatic process; AISE-P407; CS3-u1; Polish / impregnating agent. Spray and wipe manual process; AISE-P408; Professional use of maintenance	Covers use up to 8 h/day Local exhaust ventilation; No. Respiratory protection; No. Consumer protection; dermal; No. Covers skin contact area up to ; Two hands (960 cm2)

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

products; CS9-u; Stainless steel care. Manual process; AISE-P608 (PROC 10)	
Professional use of maintenance products; CS5-u2; Furniture care product. Spray and wipe manual process; AISE-P602; CS7-u2; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609 (PROC 11)	Covers use up to 0.25 h/day Local exhaust ventilation; No. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Consumer protection; dermal; No. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2)
Professional use of maintenance products; CS3-u2; Polish / impregnating agent. Spray and wipe manual process; AISE-P408 (PROC 11)	Covers use up to 1 h/day Local exhaust ventilation; No. Wear a respirator which reduces the air impurities by at least a factor of 10 (APF >= 10). For further specification, refer to section 8 of the SDS Consumer protection; dermal; No. Covers skin contact area up to ; Assumes 2 hands and forearms (1500 cm2)
Professional uses; Mixing or blending in batch processes; Uses in cosmetics/personal care products, perfumes and fragrances (PROC 5)	Covers use up to 8 h/day Local exhaust ventilation Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No.
Professional uses; Transfer of substance or mixture (charging/discharging) at non dedicated-facilities; Uses in cosmetics/personal care products, perfumes and fragrances (PROC 8a)	Covers use up to 8 h/day Local exhaust ventilation; No. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands.; For further specification, refer to section 8 of the SDS. Respiratory protection; No.

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: GES 5; Professional end-use of polishes and wax blends (ERC 8a)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

5.3.2. Worker exposure: Professional use of maintenance products; CS8-u; Leather care product. Automatic process; AISE-P605 (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.03
Inhalation, systemic, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.118
Inhalation, local, long term	2.089 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, local, acute	8.355 mg/m ³ (TRA Workers 3.0)	0.047
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.02 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.036

5.3.3. Worker exposure: Professional use of maintenance products; CS8-p; Leather care

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

product. Automatic process; AISE-P605 (PROC 8b)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	0.137 mg/kg bw/day (TRA Workers 3.0)	< 0.01
Dermal, local, long term	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	1E-2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.019

5.3.4. Worker exposure: Professional use of maintenance products; CS4-u; Furniture care product. Manual process; AISE-P601; Furniture care product. Spray and wipe manual process; AISE-P602; CS6-u; Leather care product. Manual process; AISE-P603; CS7-u1; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.089
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	6.266 mg/m ³ (TRA Workers 3.0)	0.036
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	2.743 mg/kg bw/day (TRA Workers 3.0)	0.137
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.226

5.3.5. Worker exposure: Professional use of floor care products; CS1-u; Polish / impregnating agent. Manual process; AISE-P406; Polish / impregnating agent. Semi-Automatic process; AISE-P407; CS3-u1; Polish / impregnating agent. Spray and wipe manual process; AISE-P408; Professional use of maintenance products; CS9-u; Stainless steel care. Manual process; AISE-P608 (PROC 10)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.148
Inhalation, systemic, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.592
Inhalation, local, long term	10.44 mg/m ³ (TRA Workers 3.0)	0.059
Inhalation, local, acute	41.77 mg/m ³ (TRA Workers 3.0)	0.237
Dermal, systemic, long term	2.743 mg/kg bw/day (TRA Workers 3.0)	0.137
Dermal, local, long term	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.2 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.285

5.3.6. Worker exposure: Professional use of maintenance products; CS5-u2; Furniture care product. Spray and wipe manual process; AISE-P602; CS7-u2; Leather care product. Spray and wipe manual process; AISE-P604; CS10-u1; Stainless steel care. Spray and wipe manual process; AISE-P609 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.418 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	10.71 mg/kg bw/day (TRA Workers 3.0)	0.536
Dermal, local, long term	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.542

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

5.3.7. Worker exposure: Professional use of maintenance products; CS3-u2; Polish / impregnating agent. Spray and wipe manual process; AISE-P408 (PROC 11)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.835 mg/m ³ (TRA Workers 3.0)	0.012
Inhalation, systemic, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.237
Inhalation, local, long term	0.835 mg/m ³ (TRA Workers 3.0)	< 0.01
Inhalation, local, acute	16.71 mg/m ³ (TRA Workers 3.0)	0.095
Dermal, systemic, long term	10.71 mg/kg bw/day (TRA Workers 3.0)	0.536
Dermal, local, long term	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Dermal, local, acute	0.5 mg/cm ² (TRA Workers 3.0)	< 0.01
Combined, systemic, long term		0.548

5.3.8. Worker exposure: Professional uses; Mixing or blending in batch processes; Uses in cosmetics/personal care products, perfumes and fragrances (PROC 5)

5.3.9. Worker exposure: Professional uses; Transfer of substance or mixture (charging/discharging) at non dedicated-facilities; Uses in cosmetics/personal care products, perfumes and fragrances (PROC 8a)

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

6. ES 6: Consumer use; Washing and Cleaning Products

6.1. Title section

ES name: GES 6; Consumer end-use of washing and cleaning products
Product category: Washing and Cleaning Products (PC 35)

Environment	
1: GES 6; Consumer end-use of washing and cleaning products	ERC 8d, ERC 8a
Consumer	
2: CS1; Consumer uses; Laundry and dish washing products; LAUNDRY REGULAR (powder, liquid) for consumer use; AISE-C1; LAUNDRY COMPACT (powder, liquid/gel, tablet) for consumer use; AISE-C2; FABRIC CONDITIONERS (liquid regular, liquid concentrate) for consumer use; AISE-C3; LAUNDRY ADDITIVES (powder bleach, liquid bleach, tablet) for consumer use; AISE-C4; Hand dishwashing (liquid regular, liquid concentrate) for consumer use; AISE-C5; Machine dishwashing (powder, liquid, tablet) for consumer use; AISE-C6; LAUNDRY AIDS (ironing aids-starch spray, ironing aids-other) for consumer use; AISE-C12	PC 35
3: CS2; Consumer uses; Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; TOILET CLEANERS (powder, liquid, gel, tablet) for consumer use; AISE-C8; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; WIPES (bathroom, kitchen, floor) for consumer use; AISE-C15; High Pressure washers/cleaners; AISE-C21; Automotive Care (spray, liquid); AISE-C22	PC 35
4: CS3; Consumer uses; Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; OVEN CLEANERS (spray, trigger) for consumer use; AISE-C10; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; Automotive Care	PC 35

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

(spray, liquid); AISE-C22

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: GES 6; Consumer end-use of washing and cleaning products (ERC 8d, ERC 8a)

Amount used, frequency and duration of use (or from service life)

Daily local widespread use amount; <=; 5.5E-5; tonnes/day

Other conditions affecting environmental exposure

Municipal sewage treatment plant is assumed.

6.2.2. Control of consumer exposure: CS1; Consumer uses; Laundry and dish washing products; LAUNDRY REGULAR (powder, liquid) for consumer use; AISE-C1; LAUNDRY COMPACT (powder, liquid/gel, tablet) for consumer use; AISE-C2; FABRIC CONDITIONERS (liquid regular, liquid concentrate) for consumer use; AISE-C3; LAUNDRY ADDITIVES (powder bleach, liquid bleach, tablet) for consumer use; AISE-C4; Hand dishwashing (liquid regular, liquid concentrate) for consumer use; AISE-C5; Machine dishwashing (powder, liquid, tablet) for consumer use; AISE-C6; LAUNDRY AIDS (ironing aids-starch spray, ironing aids-other) for consumer use; AISE-C12 (PC 35)

Product (article) characteristics

Covers concentrations up to 0.15 %

Physical form of product; Liquids

Exposure route; dermal; Yes

Inhalation exposure is considered to be not relevant.

Oral exposure is considered to be not relevant.

Amount used (or contained in articles), frequency and duration of use/exposure

Covers use up to 1 events per day

Frequency of use over a year; Frequent

Information and behavioral advice for consumers

Covers adult use.

Other conditions affecting consumers exposure

Assumes that potential dermal contact is limited to hands.

transfer factor; dermal; =; 1

6.2.3. Control of consumer exposure: CS2; Consumer uses; Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; TOILET CLEANERS (powder, liquid, gel, tablet) for consumer use; AISE-C8; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; WPES (bathroom, kitchen, floor) for consumer use; AISE-C15; High Pressure washers/cleaners; AISE-C21; Automotive Care (spray, liquid); AISE-C22 (PC 35)

Product (article) characteristics

Physical form of product; Liquids

Covers concentrations up to 0.1 %

Exposure route; dermal; Yes

Inhalation exposure is considered to be not relevant.

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Oral exposure is considered to be not relevant.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers use up to 1 events per day
Frequency of use over a year; Frequent
Information and behavioral advice for consumers
Covers adult use.
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to hands. transfer factor; dermal; =; 1

6.2.4. Control of consumer exposure: CS3; Consumer uses; Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; OVEN CLEANERS (spray, trigger) for consumer use; AISE-C10; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; Automotive Care (spray, liquid); AISE-C22 (PC 35)

Product (article) characteristics
Physical form of product; Liquids
Covers concentrations up to 0.1 %
Exposure route; dermal; Yes
Exposure route; Inhalation; Yes
No spraying
Oral exposure is considered to be not relevant.
Amount used (or contained in articles), frequency and duration of use/exposure
Exposure duration = 0.2 h/event
Covers use up to 1 events per day
For each use event, covers use amounts up to 30 g/event
Frequency of use over a year; Frequent
Information and behavioral advice for consumers
Indoor use
Covers adult use.
Other conditions affecting consumers exposure
Assumes that potential dermal contact is limited to hands. transfer factor; Inhalation; =; 1 transfer factor; dermal; =; 1

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: GES 6; Consumer end-use of washing and cleaning products (ERC 8d)

Release route	Release rate	Release estimation method
Water	0.055 kg/day	ERC
Air	0.055 kg/day	ERC
Soil	0.011 kg/day	ERC

Protection target	Exposure estimate	RCR
Fresh water	2.91E-3 mg/L (EUSES 2.1.2)	0.066
Sediment (freshwater)	0.058 mg/kg dw (EUSES 2.1.2)	0.066

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Marine water	2.89E-4 mg/L (EUSES 2.1.2)	0.066
Sediment (marine water)	5.79E-3 mg/kg dw (EUSES 2.1.2)	0.066
Sewage Treatment Plant	0.027 mg/L (EUSES 2.1.2)	< 0.01
Agricultural soil	7.75E-3 mg/kg dw (EUSES 2.1.2)	0.052

6.3.2. Consumer exposure: CS1; Consumer uses; Laundry and dish washing products; LAUNDRY REGULAR (powder, liquid) for consumer use; AISE-C1; LAUNDRY COMPACT (powder, liquid/gel, tablet) for consumer use; AISE-C2; FABRIC CONDITIONERS (liquid regular, liquid concentrate) for consumer use; AISE-C3; LAUNDRY ADDITIVES (powder bleach, liquid bleach, tablet) for consumer use; AISE-C4; Hand dishwashing (liquid regular, liquid concentrate) for consumer use; AISE-C5; Machine dishwashing (powder, liquid, tablet) for consumer use; AISE-C6; LAUNDRY AIDS (ironing aids-starch spray, ironing aids-other) for consumer use; AISE-C12 (PC 35)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Inhalation, local, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Dermal, systemic, long term	0.214 mg/kg bw/day (TRA Consumers 3.1)	0.021
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.021

6.3.3. Consumer exposure: CS2; Consumer uses; Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; TOILET CLEANERS (powder, liquid, gel, tablet) for consumer use; AISE-C8; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; WPES (bathroom, kitchen, floor) for consumer use; AISE-C15; High Pressure washers/cleaners; AISE-C21; Automotive Care (spray, liquid); AISE-C22 (PC 35)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Inhalation, local, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Dermal, systemic, long term	0.143 mg/kg bw/day (TRA Consumers 3.1)	0.014
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.014

6.3.4. Consumer exposure: CS3; Consumer uses; Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners); Surface cleaners (liquid, powder, gel neat, spray neat) for consumer use; AISE-C7; OVEN CLEANERS (spray, trigger) for consumer use; AISE-C10; CARPET CLEANERS (spray, liquid) for consumer use; AISE-C11; Automotive Care (spray, liquid); AISE-C22 (PC 35)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.134 mg/m ³ (TRA Consumers 3.1)	< 0.01
Inhalation, local, long term	0.134 mg/m ³ (TRA Consumers 3.1)	< 0.01
Dermal, systemic, long term	0.143 mg/kg bw/day (TRA Consumers 3.1)	0.014
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.022

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The environmental exposure to all end-use products (professional and consumer) has been combined. Some products will be completely discharged down the drain (rinse-off cosmetics, laundry detergents) whereas others will not be discharged to the sewer (shoe polish, dry cleaning). By nature air fresheners will end up in the air. By using 100% release to water and 100% to air, all consumer end-use products can be covered in one scenario. The main use of products containing fragrance substances is ERC8a (wide dispersive indoor use). The IFRA guideline (2012) also identifies ERC8d (wide dispersive outdoor use) as being relevant for the consumer end-use of washing and cleaning products (GES6) and consumer end-use of biocides (GES 8). Release rates are more conservative for ERC8d. The release factors to water and air are the same as ERC8a but an additional release of 20% to soil is assumed in the ERC for outdoor use. Therefore the assessment on the basis of ERC8d covers

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

also ERC8a

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

7. ES 7: Consumer use; Air care products

7.1. Title section

ES name: GES 7; Consumer end-use of air care products
Product category: Air care products (PC 3)

Environment	
1: GES 7; Consumer end-use of air care products	ERC 8a
Consumer	
2: CS1; Consumer uses; AIR FRESHENERS AEROSOL (aqueous, non aqueous, concentrated (mini-aerosol, Timed-release aerosols) for consumer use; AISE-C17	PC 3
3: CS2; Consumer uses; AIR FRESHENERS NON AEROSOL (perfume in/on solid substate (gel), candles, diffusers (heated) for consumer use; AISE-C18	PC 3

7.2. Conditions of use affecting exposure

7.2.1. Control of environmental exposure: GES 7; Consumer end-use of air care products (ERC 8a)

Amount used, frequency and duration of use (or from service life)
Daily local widespread use amount; <=; 0; tonnes/day

7.2.2. Control of consumer exposure: CS1; Consumer uses; AIR FRESHENERS AEROSOL (aqueous, non aqueous, concentrated (mini-aerosol, Timed-release aerosols) for consumer use; AISE-C17 (PC 3)

Product (article) characteristics
Covers concentrations up to 0.5 %
Physical form of product; Liquid for spraying (spraying can)
Exposure route; dermal; No.
Exposure route; Inhalation; Yes
Spraying
Oral exposure is considered to be not relevant.
Amount used (or contained in articles), frequency and duration of use/exposure
Exposure duration = 0.25 h/event
Covers use up to 1 events per day
For each use event, covers use amounts up to 10 g/event
Frequency of use over a year; Frequent
Information and behavioral advice for consumers
Indoor use
Covers adult use.
Other conditions affecting consumers exposure
transfer factor; Inhalation; =; 1

Administrative information:
Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

7.2.3. Control of consumer exposure: CS2; Consumer uses; AIR FRESHENERS NON AEROSOL (perfume in/on solid substate (gel), candles, diffusers (heated) for consumer use; AISE-C18 (PC 3)

Product (article) characteristics
Physical form of product; Liquids
Covers concentrations up to 0.1 %
Exposure route; dermal; Yes
Inhalation exposure is considered to be not relevant.
Oral exposure is considered to be not relevant.
Amount used (or contained in articles), frequency and duration of use/exposure
Covers use up to 1 events per day
Frequency of use over a year; Frequent
Information and behavioral advice for consumers
Covers adult use.
Other conditions affecting consumers exposure
Body parts potentially exposed; Assumes that potential dermal contact is limited to fingertips. transfer factor; dermal; =; 1

7.3. Exposure estimation and reference to its source

7.3.1. Environmental release and exposure: GES 7; Consumer end-use of air care products (ERC 8a)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

7.3.2. Consumer exposure: CS1; Consumer uses; AIR FRESHENERS AEROSOL (aqueous, non aqueous, concentrated (mini-aerosol, Timed-release aerosols) for consumer use; AISE-C17 (PC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	2.174 mg/m ³ (TRA Consumers 3.1)	0.125
Inhalation, local, long term	2.174 mg/m ³ (TRA Consumers 3.1)	0.05
Dermal, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.125

7.3.3. Consumer exposure: CS2; Consumer uses; AIR FRESHENERS NON AEROSOL (perfume in/on solid substate (gel), candles, diffusers (heated) for consumer use; AISE-C18 (PC 3)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Inhalation, local, long term	0 mg/m ³ (TRA Consumers 3.1)	< 0.01
Dermal, systemic, long term	2.5E-3 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		< 0.01

7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.
Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

8. ES 8: Consumer use; Biocidal Products

8.1. Title section

ES name: GES 8; Consumer end-use of biocides
Product category: Biocidal Products (PC 8)

Environment

1: GES 8; Consumer end-use of biocides ERC 8d

Consumer

2: CS1; Consumer uses; INSECTICIDES (liquid electric, spray neat); AISE-C19 PC 8
3: CS2; Consumer uses; REPELLENTS for consumer use; AISE-C19 PC 8

8.2. Conditions of use affecting exposure

8.2.1. Control of environmental exposure: GES 8; Consumer end-use of biocides (ERC 8d)

Amount used, frequency and duration of use (or from service life)

Daily local widespread use amount; <=; 0; tonnes/day

8.2.2. Control of consumer exposure: CS1; Consumer uses; INSECTICIDES (liquid electric, spray neat); AISE-C19 (PC 8)

Product (article) characteristics

Covers concentrations up to 0.5 %

Physical form of product; Liquids

Exposure route; dermal; Yes

Exposure route; Inhalation; Yes

No spraying

Oral exposure is considered to be not relevant.

Amount used (or contained in articles), frequency and duration of use/exposure

Exposure duration = 0.02 h/event

Covers use up to 1 events per day

For each use event, covers use amounts up to 20 g/event

Frequency of use over a year; Covers use up to ; 2; weeks per year

Information and behavioral advice for consumers

Indoor use

Covers adult use.

Other conditions affecting consumers exposure

Assumes that potential dermal contact is limited to upper part of the body.

transfer factor; Inhalation; =; 1

transfer factor; dermal; =; 1

8.2.3. Control of consumer exposure: CS2; Consumer uses; REPELLENTS for consumer use;

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

AISE-C19 (PC 8)

Product (article) characteristics

Physical form of product; Liquids
Covers concentrations up to 0.5 %
Exposure route; dermal; Yes
Exposure route; Inhalation; Yes
Spraying
Oral exposure is considered to be not relevant.

Amount used (or contained in articles), frequency and duration of use/exposure

Exposure duration = 0.02 h/event
Covers use up to 1 events per day
For each use event, covers use amounts up to 20 g/event
Frequency of use over a year; Covers use up to ; 2; weeks per year

Information and behavioral advice for consumers

Outdoor use
Covers adult use.

Other conditions affecting consumers exposure

Assumes that potential dermal contact is limited to upper part of the body.
transfer factor; Inhalation; =; 1
transfer factor; dermal; =; 1

8.3. Exposure estimation and reference to its source

8.3.1. Environmental release and exposure: GES 8; Consumer end-use of biocides (ERC 8d)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

8.3.2. Consumer exposure: CS1; Consumer uses; INSECTICIDES (liquid electric, spray neat); AISE-C19 (PC 8)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.494 mg/m ³ (TRA Consumers 3.1)	0.028
Inhalation, local, long term	0.494 mg/m ³ (TRA Consumers 3.1)	0.011
Dermal, systemic, long term	7.292 mg/kg bw/day (TRA Consumers 3.1)	0.729
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.758

8.3.3. Consumer exposure: CS2; Consumer uses; REPELLENTS for consumer use; AISE-C19 (PC 8)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.952 mg/m ³ (TRA Consumers 3.1)	0.055
Inhalation, local, long term	0.952 mg/m ³ (TRA Consumers 3.1)	0.022
Dermal, systemic, long term	7.292 mg/kg bw/day (TRA Consumers 3.1)	0.729
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.784

8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38
Sales & Distribution Information: VE01/FR/CH11/01
Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.
Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

9. ES 9: Consumer use; Polishes and Wax Blends

9.1. Title section

ES name: GES 9; Consumer end-use of polishes and wax blends
Product category: Polishes and Wax Blends (PC 31)

Environment

1: GES 9; Consumer end-use of polishes and wax blends ERC 8a

Consumer

2: CS1; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 PC 31
3: CS2; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 PC 31

9.2. Conditions of use affecting exposure

9.2.1. Control of environmental exposure: GES 9; Consumer end-use of polishes and wax blends (ERC 8a)

Amount used, frequency and duration of use (or from service life)

Daily local widespread use amount, <=, 0; tonnes/day

9.2.2. Control of consumer exposure: CS1; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 (PC 31)

Product (article) characteristics

Covers concentrations up to 0.5 %

Physical form of product; Liquids

Exposure route; dermal; Yes

Exposure route; Inhalation; Yes

No spraying

Oral exposure is considered to be not relevant.

Amount used (or contained in articles), frequency and duration of use/exposure

Exposure duration = 4 h/event

Covers use up to 1 events per day

For each use event, covers use amounts up to 10 g/event

Frequency of use over a year; Frequent

Information and behavioral advice for consumers

Indoor use

Covers adult use.

Other conditions affecting consumers exposure

Assumes that potential dermal contact is limited to inside hands / one hand / palm of hands.

transfer factor; Inhalation; =;

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

transfer factor; dermal; =; 1

9.2.3. Control of consumer exposure: CS2; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 (PC 31)

Product (article) characteristics

Physical form of product; Liquids

Covers concentrations up to 0.35 %

Exposure route; dermal; Yes

Exposure route; Inhalation; Yes

Spraying

Oral exposure is considered to be not relevant.

Amount used (or contained in articles), frequency and duration of use/exposure

Exposure duration = 1 h/event

Covers use up to 1 events per day

For each use event, covers use amounts up to 135 g/event

Frequency of use over a year; Covers use up to ; 2; weeks per year

Information and behavioral advice for consumers

Indoor use

Other conditions affecting consumers exposure

Assumes that potential dermal contact is limited to inside hands / one hand / palm of hands.

transfer factor; Inhalation; =; 1

transfer factor; dermal; =; 1

9.3. Exposure estimation and reference to its source

9.3.1. Environmental release and exposure: GES 9; Consumer end-use of polishes and wax blends (ERC 8a)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

9.3.2. Consumer exposure: CS1; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 (PC 31)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.074 mg/m ³ (TRA Consumers 3.1)	< 0.01
Inhalation, local, long term	0.074 mg/m ³ (TRA Consumers 3.1)	< 0.01
Dermal, systemic, long term	0.357 mg/kg bw/day (TRA Consumers 3.1)	0.036
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01
Combined, systemic, long term		0.04

9.3.3. Consumer exposure: CS2; Consumer uses; Polishes and wax blends; FURNITURE FLOOR and LEATHER CARE (spray, liquid) for consumer use; AISE-C20 (PC 31)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	14.76 mg/m ³ (TRA Consumers 3.1)	0.849
Inhalation, local, long term	14.76 mg/m ³ (TRA Consumers 3.1)	0.34
Oral, systemic, long term	0 mg/kg bw/day (TRA Consumers 3.1)	< 0.01

9.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

10. ES 10: Consumer use; Various products; Consumer (and Professional) end-use of cosmetics

10.1. Title section

ES name: GES 10; Consumer (and Professional) end-use of cosmetics; Only includes environmental exposure, assessment of human exposure is exempt from REACH as it is already covered by the European Cosmetic Regulation No 1223/2009

Product category: Perfumes, Fragrances (PC 28), Cosmetics, personal care products (PC 39)

Environment	
1: GES 10; Consumer (and Professional) end-use of cosmetics	ERC 8a
Consumer	
2: Perfumes, fragrances	PC 28
3: Cosmetics, personal care products	PC 39

10.2. Conditions of use affecting exposure

10.2.1. Control of environmental exposure: GES 10; Consumer (and Professional) end-use of cosmetics (ERC 8a)

Amount used, frequency and duration of use (or from service life)
Daily local widespread use amount; <=; 0; tonnes/day

10.2.2. Control of consumer exposure: Perfumes, fragrances (PC 28)

Product (article) characteristics
Covers concentrations up to 100 %
Physical form of product; Liquids

10.2.3. Control of consumer exposure: Cosmetics, personal care products (PC 39)

Product (article) characteristics
Covers concentrations up to 100 %
Physical form of product; Liquids

10.3. Exposure estimation and reference to its source

10.3.1. Environmental release and exposure: GES 10; Consumer (and Professional) end-use of cosmetics (ERC 8a)

Release route	Release rate	Release estimation method
Water	0 kg/day	ERC
Air	0 kg/day	ERC
Soil	0 kg/day	ERC

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364

Stemone - GIVAUDAN

Version 12.1

Revision Date 14 JUL 2023

Print Date 14 JUL 2023

10.3.2. Consumer exposure: Perfumes, fragrances (PC 28)

10.3.3. Consumer exposure: Cosmetics, personal care products (PC 39)

10.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance: The total tonnage of all end-uses is covered under GES6. Since the products used by professionals will not differ much from those used by consumers and since the conditions of environmental release are very similar for professionals and consumers, potential environmental exposure to the substance due to professional and private use was combined under GES6.

Scaling instructions: As the environmental release factor depends on site specific operational conditions and risk management measures, Downstream Users (DU) are advised to demonstrate that a safe use is given for the amounts used at their site. Scaling may be a suitable option in this case, (ECHA Guidance for downstream users and Guidance on the compilation of safety data sheets). Scaling is a comparison of linear input parameters and determinants between data presented in the Exposure Scenario (ES) and the data available from the Downstream User to determine the risk characterisation ratios (RCR) under the operational conditions of the DU (eg. quantity of substance used per year and site, emission fraction to water, number of emission days).

Administrative information:

Report Information: SDS_EU/EN/GHS_SDS_EU_REGION/38

Sales & Distribution Information: VE01/FR/CH11/01

Shipping Order Information: 27 410 973/22 908 364